



Bearing No. NJ416

|            |           |
|------------|-----------|
| C          | 48 mm     |
| d          | 80 mm     |
| D          | 200 mm    |
| B          | 48 mm     |
| B2         | -         |
| Cu         | 45.2      |
| Ew         | -         |
| d1         | -         |
| B1         | -         |
| Cr         | 374       |
| Fw         | 110 mm    |
| C0r        | 315       |
| r min.     | 3 mm      |
| Weight     | 7.28 Kg   |
| r(min)     | 3         |
| da(min)    | -         |
| db(min)    | 93        |
| db(max)    | 109       |
| dc(min)    | -         |
| r1(min)    | 3         |
| dd(min)    | -         |
| Da(max)    | 187       |
| Db(max)    | -         |
| Db(min)    | -         |
| r1 min.    | 3 mm      |
| ra(max)    | 2.5       |
| rb(max)    | 2.5       |
| Oil lub.   | 4200      |
| Size (mm)  | 80x200x48 |
| Width (mm) | 48        |
|            |           |

|                               |            |
|-------------------------------|------------|
| Grease lub.                   | 3100       |
| Bearing No.                   | NJ416      |
| Bearing number                | NJ416      |
| (Refer.)Mass(kg)              | 7.45       |
| Bore Diameter (mm)            | 80         |
| Outer Diameter (mm)           | 200        |
| (Grease) Lubrication Speed    | 3100 r/min |
| Basic static load rating (C0) | 315 kN     |
| Basic dynamic load rating (C) | 302 kN     |