



Bearing No. 6306DDU

r	1.1
d	30 mm
D	72 mm
B	19 mm
C	19 mm
D_	72
C0	15
Z_	8
ra	1
fo	13.3
B_	19
DI_	40.094
SRI	6.01
SRE	6.25
DE_	63.906
DA_	11.906
D_a	65.5
KBRG	6161
SBRG	3
SRIN	0
bomp	0
SREX	0.05
yobi	6306DDU
SRIX	0.025
Bore	1.181 Inch 30 Millimeter
SDM_	52
SREN	0
mass	0.345
Noun	Bearing

LangID	1
UNSPSC	31171504
da min	36.5
ALPHA_	0
r min.	1,1 mm
Weight	0,345 Kg
C_conv	26700
da max	42,5 mm
Da max.	65,5 mm
ra max.	1 mm
GRS rpm	6700
da min.	36,5 mm
hidYobi	6306DDU
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Size (mm)	30x72x19
Enclosure	2 Seals
Snap Ring	No
Inventory	0.0
Width (mm)	19
Prod_Type3	DGBB_SR_DD
Weight / LBS	0.76058
Inch - Metric	Metric
Product Group	B00308
Cage Material	Steel
Bearing number	6306DDU
Keyword String	Ball
Other Features	Deep Groove Rubber Seal
Enclosure Type	Contact Seal
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Inner Race Width	0 Inch 0 Millimeter

Outer Race Width	0.748 Inch 19 Millimeter
Long Description	30MM Bore; 72MM Outside Diameter; 19MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage;
Manufacturer URL	http://www.nskamericas.com
Outside Diameter	2.835 Inch 72 Millimeter
Manufacturer Name	NSK
Weight / Kilogram	0.345
Internal Clearance	C0-Medium
Bore Diameter (mm)	30
Outer Diameter (mm)	72
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6306DDU
Internal Special Features	No
(Grease) Lubrication Speed	6 700 r/min
Basic static load rating (C0)	15 kN
Basic dynamic load rating (C)	26,7 kN
Maximum Capacity / Filling Slot	No