



Bearing No. 695AZZ

D	13,000 mm
d	5,000 mm
B	4,000 mm
C	4,000 mm
Noun	Bearing
Bore	0.197 Inch 5 Millimeter
UNSPSC	31171504
Category	Single Row Ball Bearing
Enclosure	2 Metal Shields
Size (mm)	5x13x4
Snap Ring	No
Inventory	0.0
bore type:	Round
Width (mm)	4,000
Product Group	B00308
Inch - Metric	Metric
closure type:	Double Shielded
Cage Material	Steel
bore diameter:	5 mm
overall width:	4 mm
Keyword String	Ball
cage material:	Steel
Bearing number	695AZZ
Other Features	Deep Groove
fillet radius:	0.2 mm
finish/coating:	Uncoated
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
Long Description	5MM Bore; 13MM Outside Diameter; 4MM Outer Race Width; 2

	Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel
Manufacturer URL	http://www.ntnamerica.com
Inner Race Width	0 Inch 0 Millimeter
Outer Race Width	0.157 Inch 4 Millimeter
Outside Diameter	0.512 Inch 13 Millimeter
outer ring width:	4 mm
inner ring width:	4 mm
bearing material:	High Carbon Chrome Steel
Manufacturer Name	NTN
outside diameter:	13 mm
precision rating:	ISO Class 0
Weight / Kilogram	0.002
Bore Diameter (mm)	5,000
Internal Clearance	C0-Medium
Outer Diameter (mm)	13,000
snap ring included:	Without Snap Ring
internal clearance:	CN
Minimum Buy Quantity	N/A
maximum rpm (grease):	40000 rpm
static load capacity:	430 N
row type & fill slot:	Single Row Non-Fill Slot
dynamic load capacity:	1080 N
Harmonized Tariff Code	8482.10.50.68
Internal Special Features	No
manufacturer product page:	Click here

operating temperature range:	-40 to 120 °C
Maximum Capacity / Filling Slot	No