




Bearing No. 6308LLBNR

D	90,000 mm
C	23,000 mm
B	23,000 mm
d	40,000 mm
Noun	Bearing
Bore	1.575 Inch 40 Millimeter
UNSPSC	31171504
Category	Single Row Ball Bearing
Snap Ring	Yes
Inventory	0.0
Enclosure	2 Seals
Size (mm)	40x90x23
Width (mm)	23,000
bore type:	Round
Weight / LBS	1.411
closure type:	Double Sealed
Inch - Metric	Metric
Cage Material	Steel
Product Group	B00308
Bearing number	6308LLBNR
Keyword String	Ball
bore diameter:	40 mm
cage material:	Steel
overall width:	23 mm
Other Features	Deep Groove Non-Friction Nitrile Rubber Seal With Snap Ring Shell Alvania Prelubricated
Enclosure Type	Non-Contact Seal
fillet radius:	1.5 mm

finish/coating:	Uncoated
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
Long Description	40MM Bore; 90MM Outside Diameter; 23MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; Yes Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage;
Outside Diameter	3.543 Inch 90 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Outer Race Width	0.906 Inch 23 Millimeter
Manufacturer URL	http://www.ntnamerica.com
outer ring width:	23 mm
Weight / Kilogram	0
outside diameter:	90 mm
precision rating:	ISO Class 0
inner ring width:	23 mm
Manufacturer Name	NTN
bearing material:	High Carbon Chrome Steel
Bore Diameter (mm)	40,000
Internal Clearance	C0-Medium
snap ring included:	With Snap Ring
internal clearance:	CN
Outer Diameter (mm)	90,000
Minimum Buy Quantity	N/A
row type & fill slot:	Single Row Non-Fill Slot
maximum rpm (grease):	7800 rpm

static load capacity:	24000 N
dynamic load capacity:	40500 N
Harmonized Tariff Code	8482.10.50.68
Internal Special Features	No
manufacturer product page:	Click here
operating temperature range:	-40 to 120 °C
Maximum Capacity / Filling Slot	No