



Bearing No. 6919

r	1.1
d	95 mm
D	130 mm
B	18 mm
C	18 mm
fo	16.6
C0	33.5
ra	1
B_	18
Z_	19
D_	130
SRI	5.34
DA_	10.319
SRE	5.34
DE_	122.819
DI_	102.181
D_a	123.5
SREN	-0.025
Bore	3.74 Inch 95 Millimeter
SRIN	-0.025
mass	0.601
bomp	0
Noun	Bearing
yobi	6919
SRIX	0.025
SDM_	112.5
SREX	0.025
KBRG	6101
SBRG	19
C_conv	33500

ALPHA_	0
Weight	0,601 Kg
da max	103,5 mm
r min.	1,1 mm
da min	101.5
UNSPSC	31171504
LangID	1
hidYobi	6919
GRS rpm	4800
Oil rpm	5600
Da max.	123,5 mm
ra max.	1 mm
da min.	101,5 mm
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Size (mm)	95x130x18
Snap Ring	No
Enclosure	Open
Inventory	0.0
Width (mm)	18
Prod_Type3	DGBB_SR_OT
Weight / LBS	1.3252
Inch - Metric	Metric
Cage Material	Steel
Product Group	B00308
Bearing number	6919
Keyword String	Ball
Other Features	Deep Groove
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
Outside Diameter	5.118 Inch 130 Millimeter
Long Description	95MM Bore; 130MM

	Outside Diameter; 18MM Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage
Inner Race Width	0 Inch 0 Millimeter
Outer Race Width	0.709 Inch 18 Millimeter
Manufacturer URL	http://www.nskamericas.com
Manufacturer Name	NSK
Weight / Kilogram	0.6
Internal Clearance	C0-Medium
Bore Diameter (mm)	95
Outer Diameter (mm)	130
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
(Oil) Lubrication Speed	5 600 r/min
Internal Special Features	No
(Grease) Lubrication Speed	4 800 r/min
Basic static load rating (C0)	33,5 kN
Basic dynamic load rating (C)	33,5 kN
Maximum Capacity / Filling Slot	No