




Bearing No. 6910VV

r	0.6
d	50 mm
D	72 mm
B	12 mm
C	12 mm
fo	16.1
D_	72
B_	12
ra	0.6
Z_	16
C0	11.7
DI_	54.253
SRE	3.49
D_a	68
DE_	67.747
SRI	3.49
DA_	6.747
SREN	-0.02
Bore	1.969 Inch 50 Millimeter
SRIN	-0.02
bomp	0
SRIX	0.02
yobi	6910VV
mass	0.135
SDM_	61
KBRG	6151
SREX	0.02
SBRG	19
Noun	Bearing

r min.	0,6 mm
da min	54
ALPHA_	0
UNSPSC	31171504
C_conv	14500
da max	55 mm
Weight	0,135 Kg
LangID	1
Da max.	68 mm
hidYobi	6910VV
da min.	54 mm
GRS rpm	9000
ra max.	0,6 mm
hidTable	ecat_NSRDGB
Category	Single Row Ball Bearing
Enclosure	2 Seals
Inventory	0.0
Snap Ring	No
Size (mm)	50x72x12
Prod_Type3	DGBB_SR_VV
Width (mm)	12
Weight / LBS	1.968
Inch - Metric	Metric
Cage Material	Steel
Product Group	B00308
Bearing number	6910VV
Keyword String	Ball
Enclosure Type	Non-Contact Seal
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Outer Race Width	0.472 Inch 12 Millimeter
Long Description	50MM Bore; 72MM

	Outside Diameter; 12MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Outside Diameter	2.835 Inch 72 Millimeter
Manufacturer URL	http://www.nskamericas.com
Weight / Kilogram	0.128
Manufacturer Name	NSK
Bore Diameter (mm)	50
Internal Clearance	C0-Medium
Outer Diameter (mm)	72
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Internal Special Features	No
(Grease) Lubrication Speed	9 000 r/min
Basic dynamic load rating (C)	14,5 kN
Basic static load rating (C0)	11,7 kN
Maximum Capacity / Filling Slot	No