




Bearing No. 6907ZZ

D	55 mm
d	35 mm
B	10 mm
C	10 mm
rn	0,5 mm
Bore	1.378 Inch 35 Millimeter
Noun	Bearing
Weight	0,074 Kg
r min.	0,6 mm
UNSPSC	31171504
da max	40 mm
da min.	39 mm
Da max.	51 mm
ra max.	0,6 mm
series:	69
Category	Single Row Ball Bearing
Enclosure	2 Metal Shields
Size (mm)	35x55x10
Inventory	0.0
Snap Ring	No
Width (mm)	10
bore type:	Round
maximum rpm:	12000 RPM
Weight / LBS	0.16
Cage Material	Steel
Inch - Metric	Metric
Product Group	B00308
closure type:	Double Shielded
bore diameter:	35 mm

Keyword String	Ball
overall width:	10 mm
cage material:	Steel
fillet radius:	0.6 mm
Bearing number	6907ZZ
Rolling Element	Ball Bearing
finish/coating:	Uncoated
Precision Class	ABEC 1 ISO P0
Long Description	35MM Bore; 55MM Outside Diameter; 10MM Outer Race Diameter; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Manufacturer URL	http://www.ntnamerica.com
Outside Diameter	2.165 Inch 55 Millimeter
Outer Race Width	0.394 Inch 10 Millimeter
outside diameter:	55 mm
outer ring width:	10 mm
inner ring width:	10 mm
Manufacturer Name	NTN
bearing material:	High Carbon Chrome Steel
Weight / Kilogram	0.072
precision rating:	ISO Class 0
Internal Clearance	C0-Medium
Bore Diameter (mm)	35
Outer Diameter (mm)	55
internal clearance:	CN
snap ring included:	Without Snap Ring

Minimum Buy Quantity	N/A
maximum rpm (grease):	12000 rpm
static load capacity:	6850 N
row type & fill slot:	Single Row Non-Fill Slot
dynamic load capacity:	9550 N
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6907ZZ/2AS
Internal Special Features	No
(Grease) Lubrication Speed	12 000 r/min
manufacturer product page:	Click here
operating temperature range:	-40 to 120 °C
Basic dynamic load rating (C)	9,55 kN
Basic static load rating (C0)	6,85 kN
Maximum Capacity / Filling Slot	No