




Bearing No. 6822VV

r	1
d	110 mm
D	140 mm
B	16 mm
C	16 mm
D_	140
B_	16
ra	1
C0	32.5
fo	17.1
Z_	25
DI_	116.269
SRE	4.52
D_a	135
DE_	133.731
DA_	8.731
SRI	4.52
SREN	0
SBRG	18
SREX	0.02
KBRG	6151
Bore	4.331 Inch 110 Millimeter
mass	0.497
Noun	Bearing
SRIX	0.02
SRIN	-0.02
SDM_	125
bomp	0
yobi	6822VV

Weight	0,497 Kg
LangID	1
da max	117 mm
C_conv	28100
ALPHA_	0
da min	115
UNSPSC	31171504
r min.	1 mm
hidYobi	6822VV
ra max.	1 mm
GRS rpm	4300
Da max.	135 mm
da min.	115 mm
hidTable	ecat_NSRDGB
Category	Single Row Ball Bearing
Snap Ring	No
Size (mm)	110x140x16
Enclosure	2 Seals
Inventory	0.0
Width (mm)	16
bore type:	Round
Prod_Type3	DGBB_SR_VV
Weight / LBS	0.489
Product Group	B00308
Cage Material	Steel
closure type:	Double Sealed
Inch - Metric	Metric
Bearing number	6822VV
Keyword String	Ball
overall width:	16 mm
Enclosure Type	Non-Contact Seal
bore diameter:	140 mm

Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Outside Diameter	5.512 Inch 140 Millimeter
Long Description	110MM Bore; 140MM Outside Diameter; 16MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Outer Race Width	0.63 Inch 16 Millimeter
Manufacturer URL	http://www.nskamericas.com
Manufacturer Name	NSK
Weight / Kilogram	0.6
outside diameter:	140 mm
Bore Diameter (mm)	110
Internal Clearance	C0-Medium
Outer Diameter (mm)	140
internal clearance:	Normal Clearance
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6822VV
manufacturer upc number:	029176030345
Internal Special Features	No
(Grease) Lubrication Speed	4 300 r/min
Basic static load rating (C0)	32,5 kN
Basic dynamic load rating (C)	28,1 kN
Maximum Capacity /	No

Filling Slot	
--------------	--