



Bearing No. 16048

|        |         |
|--------|---------|
| r      | 2.1     |
| d      | 240 mm  |
| D      | 360 mm  |
| B      | 37 mm   |
| C      | 37 mm   |
| C0     | 243     |
| Z_     | 18      |
| ra     | 2       |
| B_     | 37      |
| D_     | 360     |
| fo     | 16.5    |
| D_a    | 349     |
| SRE    | 14.79   |
| DE_    | 328.575 |
| DA_    | 28.575  |
| DI_    | 271.425 |
| SRI    | 14.79   |
| mass   | 13.9    |
| SRIN   | -0.05   |
| SBRG   | 0       |
| SRIX   | 0.05    |
| KBRG   | 6104    |
| SREN   | -0.05   |
| yobi   | 16048   |
| bomp   | 0       |
| SREX   | 0.05    |
| SDM_   | 300     |
| r min. | 2,1 mm  |
| ALPHA_ | 0       |
| da min | 251     |
|        |         |

|                               |             |
|-------------------------------|-------------|
| C_conv                        | 196000      |
| Weight                        | 13,9 Kg     |
| LangID                        | 1           |
| Oil rpm                       | 1900        |
| GRS rpm                       | 1500        |
| hidYobi                       | 16048       |
| ra max.                       | 2 mm        |
| Da max.                       | 342 mm      |
| da min.                       | 262 mm      |
| hidTable                      | ecat_NSRDGB |
| Size (mm)                     | 240x360x37  |
| Prod_Type3                    | DGBB_SR_OT  |
| Width (mm)                    | 37          |
| Bearing number                | 16048       |
| Bore Diameter (mm)            | 240         |
| Outer Diameter (mm)           | 360         |
| Basic static load rating (C0) | 243 kN      |
| Basic dynamic load rating (C) | 196 kN      |