



Bearing No. SL045060-PP

	WRE460 / Designation for snap ring WRE
t	3 mm
m	126 kg / Weight
d	300 mm
D	460 mm
B	218 mm
C	216 mm
X	170 mm / Distance between rolling elements
Size (mm)	300x460x218
Width (mm)	218
d ₁	346,85 mm
d ₃	493 mm / Outside diameter of snap ring WRE
d ₂	375 mm
C ₁	185,2 mm / Tolerance: +0,2
D ₁	453 mm / Tolerance: +0,2
C _r	3000000 N / Dynamic load rating (radial)
C _{0r}	5800000 N / Static load rating (radial)
C _{ur}	640000 N
Bearing number	SL045060-PP
r _{min}	1,1 mm
n _{G Fett}	340 1/min / Limiting speed for grease lubrication
Bore Diameter (mm)	300

Outer Diameter (mm)	460
C _{a1} - 176 mm / Mounting dimension for snap ring WRE / Tolerance: -0,2	176 mm / Mounting dimension for snap ring WRE / Tolerance: 0,2
C _{a2} - 171 mm / Mounting dimension for retaining ring to DIN 471 / Tolerance: -0,2	171 mm / Mounting dimension for retaining ring to DIN 471 / Tolerance: 0,2