



Bearing No. SL045026-PP

	WRE200 / Designation for snap ring WRE
t	1,8 mm
m	10,5 kg / Weight
d	130 mm
D	200 mm
B	95 mm
C	94 mm
X	77 mm / Distance between rolling elements
Size (mm)	130x200x95
Width (mm)	95
d ₁	156,75 mm
d ₃	216 mm / Outside diameter of snap ring WRE
d ₂	170 mm
C ₁	83,2 mm / Tolerance: +0,2
D ₁	196 mm / Tolerance: +0,2
C _r	540000 N / Dynamic load rating (radial)
C _{0r}	960000 N / Static load rating (radial)
C _{ur}	128000 N
Bearing number	SL045026-PP
r _{min}	0,6 mm
n _{G Fett}	800 1/min / Limiting speed for grease lubrication
Bore Diameter (mm)	130

Outer Diameter (mm)	200
C _{a1} - 77 mm / Mounting dimension for snap ring WRE / Tolerance: -0,2	77 mm / Mounting dimension for snap ring WRE / Tolerance: 0,2
C _{a2} - 75 mm / Mounting dimension for retaining ring to DIN 471 / Tolerance: -0,2	75 mm / Mounting dimension for retaining ring to DIN 471 / Tolerance: 0,2