




Bearing No. NU 2306 ECML

s	2.4 mm
d	30 mm
D	72 mm
B	27 mm
F	40.5 mm
s max.	2.4 mm
Size (mm)	72x30x27
Width (mm)	27
Mass bearing	0.59 kg
D_1	58.85 mm
Limiting speed	19000 r/min
Bearing number	NU 2306 ECML
Reference speed	11000 r/min
Limiting value e	0.3
d_a max.	39 mm
d_a min.	37 mm
Bore Diameter (mm)	72
r_a max.	1 mm
D_a max.	65.1 mm
r_b max.	1 mm
d_b min.	43 mm
Axial load factor Y	0.4
Outer Diameter (mm)	30
r_b - max.	1 mm
r_a - max.	1 mm
$r_{1,2}$ min.	1.1 mm
d_a - min.	37 mm
D_a - max.	65.1 mm
d_b - min.	43 mm
d_a - max.	39 mm

$r_{3,4}$ min.	1.1 mm
D_1 ?	58.85 mm
$r_{3,4}$ - min.	1.1 mm
$r_{1,2}$ - min.	1.1 mm
Basic dynamic load rating C	83 kN
Basic dynamic load rating - C	83 kN
Fatigue load limit P_u	9.65 kN
Calculation factor k_r	0.38
Calculation factor - k_r	0.38
Fatigue load limit - P_u	9.6 kN
Basic static load rating C_0	75 kN
Basic static load rating - C_0	75 kN