




Bearing No. NU 2220 ECJ

s	2.5 mm
F	119 mm
d	100 mm
D	180 mm
B	46 mm
Noun	Bearing
Bore	3.937 Inch 100 Millimeter
Width	1.811 Inch 46 Millimeter
UNSPSC	31171547
s max.	2.5 mm
series:	NU22
Profile	Complete with Outer and Inner Ring
flanges:	(2) Outer Ring
Category	Cylindrical Roller Bearing
Retainer	Yes
Size (mm)	180x100x46
Snap Ring	No
Separable	Inner Ring - Both Sides
Inventory	0.0
bore type:	Straight
Width (mm)	46
maximum rpm:	4550 RPM
Weight / LBS	10.752
Bore Profile	Straight
Mass bearing	4.8 kg
closure type:	Open
Product Group	B04144

D ₁	155.6 mm
Cage Material	Steel
Inch - Metric	Metric
Bearing number	NU 2220 ECJ
Relubricatable	Yes
fillet radius:	2 mm
cage material:	Steel
Limiting speed	4500 r/min
bore diameter:	100 mm
Other Features	High Capacity Plain Inner Ring 2 Rib Outer Ring Cage on Outer Ring ID
overall width:	46 mm
number of rows:	1
Rolling Element	Cylindrical Roller Bearing
finish/coating:	Uncoated
Reference speed	4000 r/min
Precision Class	RBEC 1 ISO P0
Limiting value e	0.3
Long Description	100MM Bore; Straight Bore Profile; 180MM Outside Diameter; 46MM Width; Steel Cage Matetrial; RBEC 1 ISO P0; Single Row; Inner Ring - Both Sides Separable; No Snap Ring; Relubricatable; C0-Medium Int
ring separation:	Separable Ring
Manufacturer URL	http://www.skf.com
Outside Diameter	7.087 Inch 180 Millimeter
outside diameter:	180 mm

Manufacturer Name	SKF
outer ring width:	46 mm
Weight / Kilogram	4.881
precision rating:	Not Rated
bearing material:	Steel
r _b max.	2 mm
Internal Clearance	C0-Medium
r _a max.	2 mm
D _a max.	167.5 mm
d _b min.	122 mm
d _a max.	116 mm
d _a min.	113 mm
Bore Diameter (mm)	180
Outer Diameter (mm)	100
internal clearance:	C0
Axial load factor Y	0.4
Minimum Buy Quantity	N/A
r _a - max.	2 mm
d _a - min.	113 mm
r _b - max.	2 mm
d _a - max.	116 mm
d _b - min.	122 mm
D _a - max.	167.5 mm
r _{1,2} min.	2.1 mm
r _{3,4} min.	2.1 mm
D ₁ ?	155.6 mm
static load capacity:	450 kN
r _{3,4} - min.	2.1 mm
Harmonized Tariff Code	8482.50.00.00
r _{1,2} - min.	2.1 mm
dynamic load capacity:	380 kN
Manufacturer Item Number	NU 2220 ECJ

Number of Rows of Rollers	Single Row
Basic dynamic load rating C	380 kN
operating temperature range:	Maximum of +300 °F
Basic dynamic load rating - C	380 kN
Fatigue load limit P_u	54 kN
Calculation factor k_r	0.2
Fatigue load limit - P_u	54 kN
Calculation factor - k_r	0.2
Basic static load rating C_0	450 kN
Basic static load rating - C_0	450 kN