




Bearing No. NU 2230 ECM

D	270 mm
d	150 mm
B	73 mm
F	182 mm
s	4.9 mm
Bore	5.906 Inch 150 Millimeter
Noun	Bearing
Width	2.874 Inch 73 Millimeter
s max.	4.9 mm
UNSPSC	31171547
series:	NU22
Profile	Complete with Outer and Inner Ring
flanges:	(2) Outer Ring
Retainer	Yes
Category	Cylindrical Roller Bearing
Size (mm)	270x150x73
Snap Ring	No
Inventory	0.0
Separable	Inner Ring - Both Sides
bore type:	Straight
Width (mm)	73
Bore Profile	Straight
Mass bearing	18.5 kg
application:	Piston Type Machines, Rolling Mills, Spindles/Machine Tools
Weight / LBS	41.513
maximum rpm:	2800 RPM

closure type:	Open
Inch - Metric	Metric
Product Group	B04144
Cage Material	Brass
D ₁	232.2 mm
bore diameter:	150 mm
overall width:	73 mm
cage material:	Brass
Other Features	High Capacity Plain Inner Ring 2 Rib Outer Ring Cage on Outer Ring ID
Relubricatable	Yes
fillet radius:	2.5 mm
Bearing number	NU 2230 ECM
Limiting speed	2800 r/min
Rolling Element	Cylindrical Roller Bearing
number of rows:	1
Precision Class	RBEC 1 ISO P0
finish/coating:	Uncoated
Reference speed	2600 r/min
Outside Diameter	10.63 Inch 270 Millimeter
Limiting value e	0.3
Long Description	150MM Bore; Straight Bore Profile; 270MM Outside Diameter; 73MM Width; Brass Cage Matetrial; RBEC 1 ISO P0; Single Row; Inner Ring - Both Sides Separable; No Snap Ring; Relubricatable; C0-Medium Int
Manufacturer URL	http://www.skf.com

ring separation:	Separable Ring
bearing material:	Steel
outside diameter:	270 mm
precision rating:	RBEC 1 (ISO Class Normal)
outer ring width:	73 mm
Weight / Kilogram	18.847
Manufacturer Name	SKF
D _a max.	254.6 mm
d _a max.	178 mm
r _a max.	2.5 mm
r _b max.	2.5 mm
d _a min.	164 mm
Bore Diameter (mm)	270
Internal Clearance	C0-Medium
d _b min.	186 mm
Outer Diameter (mm)	150
Axial load factor Y	0.4
internal clearance:	C0
r _{3,4} min.	3 mm
r _{1,2} min.	3 mm
d _a - min.	164 mm
r _a - max.	2.5 mm
Minimum Buy Quantity	N/A
r _b - max.	2.5 mm
d _a - max.	178 mm
d _b - min.	186 mm
D _a - max.	254.6 mm
static load capacity:	930 kN
D ₁ ?	232.2 mm
r _{3,4} - min.	3 mm
Harmonized Tariff Code	8482.50.00.00
	3 mm

r _{1,2} - min.	
-------------------------	--

dynamic load capacity:	735 kN
Manufacturer Item Number	NU 2230 ECM
Number of Rows of Rollers	Single Row
Basic dynamic load rating C	735 kN
operating temperature range:	Maximum of +300 °F
Basic dynamic load rating - C	735 kN
Fatigue load limit P_u	100 kN
Calculation factor k_r	0.2
Fatigue load limit - P_u	100 kN
Calculation factor - k_r	0.2
Basic static load rating C_0	930 kN
Basic static load rating - C_0	930 kN