



Bearing No. 13687/13621

e	0.4
d	38,1 mm
D	69,012 mm
T	19,05 mm
B	19,05 mm
C	15,083 mm
a	15,8 mm
Da	61 mm
B_	19.05
Db	65 mm
da	46,5 mm
Y0	0.82
db	43 mm
C0	61
D_	69.012
Z_	20
C_	15.083
Y1	1.5
DE_	60.157
SLR	12.7
D_a	61
DI_	46.406
DA1	7.5
DA2	6.727
CUP	0.104
DA_	7.115
D_b	65
RAr	122.796
SDM_	53.379
KBRG	3161

yobi	13687/13621
CONE	0.193
ALP21	30
ALP22	0
ALP23	0
BETA_	1
BET21	3
BET23	0
BET22	30
r min.	2 mm
LangID	1
Weight	0,297 Kg
ALPHA_	15
r1 min.	2,3 mm
ra max.	2 mm
Oil rpm	7100
outer r	2.3
hidYobi	13687/13621
GRS rpm	5300
inner r	2
hidTable	ecat_NSTPRI
inner ra	2
outer rb	2.3
ra1 max.	2,3 mm
Size (mm)	38.1x69.012x19.05
SHOG_yobi	13687R/13621R
Prod_Type3	TRBSR_ID_A
Width (mm)	19,05
Bearing number	13687/13621
Bore Diameter (mm)	38,1
Outer Diameter (mm)	69,012
Calculation factor (e)	0,4

(Oil) Lubrication Speed	7100 r/min
Calculation factor (Y0)	0,82
(Grease) Lubrication Speed	5300 r/min
Basic static load rating (C0)	61 kN
Basic dynamic load rating (C)	49 kN