




Bearing No. NU 2218 ECP

D	160 mm
d	90 mm
B	40 mm
F	107 mm
s	2.6 mm
Bore	3.543 Inch 90 Millimeter
Noun	Bearing
Width	1.575 Inch 40 Millimeter
s max.	2.6 mm
UNSPSC	31171547
series:	NU22
Profile	Complete with Outer and Inner Ring
flanges:	(2) Outer Ring
Retainer	Yes
Category	Cylindrical Roller Bearing
Size (mm)	160x90x40
Snap Ring	No
Inventory	0.0
Separable	Inner Ring - Both Sides
bore type:	Straight
Width (mm)	40
Bore Profile	Straight
Mass bearing	3.13 kg
application:	Piston Type Machines, Rolling Mills, Spindles/Machine Tools
Weight / LBS	7.05
maximum rpm:	5000 RPM

closure type:	Open
Inch - Metric	Metric
Product Group	B04144
Cage Material	Polymer
D ₁	138.5 mm
bore diameter:	90 mm
overall width:	40 mm
cage material:	Polyamide
Other Features	High Capacity Plain Inner Ring 2 Rib Outer Ring Cage on Outer Ring ID
Relubricatable	Yes
fillet radius:	2 mm
Bearing number	NU 2218 ECP
Limiting speed	5000 r/min
Rolling Element	Cylindrical Roller Bearing
number of rows:	1
Precision Class	RBEC 1 ISO P0
finish/coating:	Uncoated
Reference speed	4500 r/min
ring separation:	Separable Ring
Manufacturer URL	http://www.skf.com
Outside Diameter	6.299 Inch 160 Millimeter
Limiting value e	0.3
Long Description	90MM Bore; Straight Bore Profile; 160MM Outside Diameter; 40MM Width; Polymer Cage Material; RBEC 1 ISO P0; Single Row; Inner Ring - Both Sides Separable; No Snap Ring; Relubricatable;

	C0-Medium In
outer ring width:	40 mm
Manufacturer Name	SKF
Weight / Kilogram	3.201
bearing material:	Steel
precision rating:	RBEC 1 (ISO Class Normal)
outside diameter:	160 mm
Internal Clearance	C0-Medium
Bore Diameter (mm)	160
r_b max.	2 mm
d_a max.	104 mm
d_b min.	110 mm
D_a max.	149 mm
r_a max.	2 mm
d_a min.	101 mm
Outer Diameter (mm)	90
Axial load factor Y	0.4
internal clearance:	C0
$r_{3,4}$ min.	2 mm
$r_{1,2}$ min.	2 mm
d_a - min.	101 mm
r_a - max.	2 mm
Minimum Buy Quantity	N/A
r_b - max.	2 mm
d_a - max.	104 mm
d_b - min.	110 mm
D_a - max.	149 mm
static load capacity:	315 kN
D_1 ?	138.5 mm
$r_{3,4}$ - min.	2 mm
Harmonized Tariff Code	8482.50.00.00
	2 mm

r_{1,2} - min.	
-----------------------------------	--

dynamic load capacity:	280 kN
Manufacturer Item Number	NU 2218 ECP
Number of Rows of Rollers	Single Row
Basic dynamic load rating C	280 kN
operating temperature range:	Maximum of +300 °F
Basic dynamic load rating - C	280 kN
Fatigue load limit P_u	39 kN
Calculation factor k_r	0.2
Fatigue load limit - P_u	39 kN
Calculation factor - k_r	0.2
Basic static load rating C_0	315 kN
Basic static load rating - C_0	315 kN