




Bearing No. 51105

D	42 mm
d	25 mm
T	11 mm
d1	42 mm
D1	26 mm
Noun	Bearing
Bore 1	0.984 Inch 25 Millimeter
Weight	0,06 Kg
Bore 2	1.024 Inch 26 Millimeter
UNSPSC	31171552
Banded	No
r min.	0,6 mm
Height	0.433 Inch 11 Millimeter
da min.	35 mm
ra max.	0,6 mm
Da max.	32 mm
series:	511
Category	Thrust Ball Bearings
Inventory	7.0
Size (mm)	25x42x11
Width (mm)	11
Weight / LBS	0.13228
maximum rpm:	6500 rpm
Product Group	B00308
Inch - Metric	Metric
Cage Material	Steel
bore diameter:	25 mm
overall width:	11 mm

Keyword String	Ball Thrust
cage material:	Resin
fillet radius:	0.6 mm
Bearing number	51105
Other Features	Single Row With Flat Seat
Thrust Bearing	Yes
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
Long Description	25MM Bore 1; 26MM Bore 2; 42MM Outside Diameter; 11MM Height; Ball Bearing; Single Direction; Not Banded; Steel Cage; ABEC 1 ISO P0 Precision
Manufacturer URL	http://www.ntnamerica.com
Outside Diameter	1.654 Inch 42 Millimeter
outside diameter:	42 mm
Manufacturer Name	NTN
Weight / Kilogram	0.052
bearing material:	High Carbon Chrome Steel
precision rating:	ISO Class 0
Bore Diameter (mm)	25
Outer Diameter (mm)	42
thrust bearing type:	Single-Direction
Minimum Buy Quantity	N/A
separable or banded:	Separable
Component Description	Roller Assembly Plus Raceways
static load capacity:	37000 N
dynamic load capacity:	19600 N
Harmonized Tariff Code	8482.10.50.08

Manufacturer Item Number	51105
outside diameter design:	Straight
(Grease) Lubrication Speed	4 600 r/min
Single or Double Direction	Single Direction
manufacturer product page:	Click here
operating temperature range:	-40 to 120 °C
Basic static load rating (C0)	37 kN
Basic dynamic load rating (C)	19,6 kN
Overall Height with Aligning Washer	0 Inch 0 Millimeter