




Bearing No. NU 2207 ECP

D	72 mm
d	35 mm
B	23 mm
F	44 mm
s	2.8 mm
Bore	1.378 Inch 35 Millimeter
Noun	Bearing
Width	0.906 Inch 23 Millimeter
s max.	2.8 mm
UNSPSC	31171547
series:	NU22
Profile	Complete with Outer and Inner Ring
flanges:	(2) Outer Ring
Retainer	Yes
Category	Cylindrical Roller Bearing
Size (mm)	72x35x23
Snap Ring	No
Inventory	4.0
Separable	Inner Ring - Both Sides
bore type:	Straight
Width (mm)	23
Bore Profile	Straight
Mass bearing	0.4 kg
application:	Piston Type Machines, Rolling Mills, Spindles/Machine Tools
Weight / LBS	0.911
maximum rpm:	12000 RPM

closure type:	Open
Inch - Metric	Metric
Product Group	B04144
Cage Material	Polymer
D ₁	60.2 mm
bore diameter:	35 mm
overall width:	23 mm
cage material:	Polyamide
Other Features	High Capacity Plain Inner Ring 2 Rib Outer Ring Cage on Outer Ring ID
Relubricatable	Yes
fillet radius:	1 mm
Bearing number	NU 2207 ECP
Limiting speed	12000 r/min
Rolling Element	Cylindrical Roller Bearing
number of rows:	1
Precision Class	RBEC 1 ISO P0
finish/coating:	Uncoated
Reference speed	11000 r/min
ring separation:	Separable Ring
Limiting value e	0.3
Long Description	35MM Bore; Straight Bore Profile; 72MM Outside Diameter; 23MM Width; Polymer Cage Matetrial; RBEC 1 ISO P0; Single Row; Inner Ring - Both Sides Separable; No Snap Ring; Relubricatable; C0-Medium Int
Manufacturer URL	http://www.skf.com
Outside Diameter	2.835 Inch 72

	Millimeter
bearing material:	Steel
outside diameter:	72 mm
precision rating:	RBEC 1 (ISO Class Normal)
outer ring width:	23 mm
Weight / Kilogram	0.414
Manufacturer Name	SKF
D _a max.	65.1 mm
d _a max.	42.2 mm
r _a max.	1 mm
r _b max.	0.6 mm
d _a min.	39.8 mm
Bore Diameter (mm)	72
Internal Clearance	C0-Medium
d _b min.	46 mm
Outer Diameter (mm)	35
Axial load factor Y	0.4
internal clearance:	C0
r _{3,4} min.	0.6 mm
r _{1,2} min.	1.1 mm
d _a - min.	39.8 mm
r _a - max.	1 mm
Minimum Buy Quantity	N/A
r _b - max.	0.6 mm
d _a - max.	42.2 mm
d _b - min.	46 mm
D _a - max.	65.1 mm
static load capacity:	63 kN
D ₁ ?	60.2 mm
r _{3,4} - min.	0.6 mm
Harmonized Tariff Code	8482.50.00.00
	1.1 mm

r _{1,2} - min.	
-------------------------	--

dynamic load capacity:	69.5 kN
Manufacturer Item Number	NU 2207 ECP
Number of Rows of Rollers	Single Row
Basic dynamic load rating C	69.5 kN
operating temperature range:	Maximum of +300 °F
Basic dynamic load rating - C	69.5 kN
Fatigue load limit P_u	8.15 kN
Calculation factor k_r	0.2
Fatigue load limit - P_u	8.2 kN
Calculation factor - k_r	0.2
Basic static load rating C_0	63 kN
Basic static load rating - C_0	63 kN