



Bearing No. 1726205-2RS1

D	52 mm
d	25 mm
B	15 mm
Bore	0.984 Inch 25 Millimeter
Noun	Bearing
UNSPSC	31171536
series:	17262
Category	Insert Bearings
Size (mm)	52x25x15
Inventory	0.0
Snap Ring	No
Seal Type	RS1 Seal
bore type:	Round
Width (mm)	15
Weight / LBS	0.243
maximum rpm:	8500 RPM
closure type:	Double Sealed
d ₁	34.35 mm
Product Group	M06110
Inch - Metric	Metric
Keyword String	Insert
Other Features	Single Row Standard Duty Metric
bore diameter:	25 mm
Bearing number	1726205-2RS1
Limiting speed	8500 r/min
Relubricatable	No
Rolling Element	Ball Bearing
finish/coating:	Uncoated
Mounting Method	Shaft Mount

Manufacturer URL	http://www.skf.com
Outside Diameter	2.047 Inch 52 Millimeter
Long Description	25MM Bore; Standard Inner Ring; Ball Bearing; 15MM Length Thru Bore; 15MM Outer Race Width; 52MM Outside Diameter; Not Relubricatable; RS1 Seal Seal; Shaft Mount Mounting Method; No Snap Ring
Length Thru Bore	0.591 Inch 15 Millimeter
Outer Race Width	0.591 Inch 15 Millimeter
outer ring width:	15 mm
Manufacturer Name	SKF
outside diameter:	52 mm
Weight / Kilogram	0.11
Bore Diameter (mm)	52
Inner Race Profile	Standard Inner Ring
Outer Race Profile	Spherical
Outer Diameter (mm)	25
snap ring included:	Without Snap Ring
internal clearance:	C0
Minimum Buy Quantity	N/A
r _{1,2} min.	1 mm
row type & fill slot:	Single Row Non-Fill Slot
d ₁ ?	34.35 mm
Mass complete bearing	0.12 kg
r _{1,2} - min.	1 mm
Harmonized Tariff Code	8482.10.50.00
Manufacturer Item Number	1726205-2RS1

Basic dynamic load rating C	14 kN
Limiting speed ¹⁾	8500 r/min
operating temperature range:	-40 to +210 °F
Basic dynamic load rating - C	14 kN
Fatigue load limit P_u	0.335 kN
Calculation factor f_0	14
Calculation factor - f_0	14
Fatigue load limit - P_u	0.335 kN
Basic static load rating C_0	7.8 kN
Basic static load rating - C_0	7.8 kN