



Bearing No. 1726308-2RS1

D	90 mm
d	40 mm
B	23 mm
Noun	Bearing
Bore	1.575 Inch 40 Millimeter
UNSPSC	31171536
series:	17263
Category	Insert Bearings
Seal Type	RS1 Seal
Size (mm)	90x40x23
Inventory	0.0
Snap Ring	No
Width (mm)	23
bore type:	Round
Weight / LBS	1.21
maximum rpm:	5000 RPM
closure type:	Double Sealed
d ₁	56.11 mm
Product Group	M06110
Inch - Metric	Metric
overall width:	23 mm
Keyword String	Insert
Other Features	Single Row Standard Duty Metric
bore diameter:	40 mm
Bearing number	1726308-2RS1
Limiting speed	5000 r/min
Relubricatable	No
Mounting Method	Shaft Mount
finish/coating:	Uncoated

Rolling Element	Ball Bearing
Long Description	40MM Bore; Standard Inner Ring; Ball Bearing; 23MM Length Thru Bore; 23MM Outer Race Width; 90MM Outside Diameter; Not Relubricatable; RS1 Seal Seal; Shaft Mount Mounting Method; No Snap Ring
Outside Diameter	3.543 Inch 90 Millimeter
Outer Race Width	0.906 Inch 23 Millimeter
Length Thru Bore	0.906 Inch 23 Millimeter
Manufacturer URL	http://www.skf.com
outer ring width:	56.1 mm
outside diameter:	90 mm
Manufacturer Name	SKF
Weight / Kilogram	0.55
Bore Diameter (mm)	90
Inner Race Profile	Standard Inner Ring
Outer Race Profile	Spherical
Outer Diameter (mm)	40
internal clearance:	C0
snap ring included:	Without Snap Ring
Minimum Buy Quantity	N/A
r _{1,2} min.	1.5 mm
Mass complete bearing	0.61 kg
d ₁ ?	56.11 mm
row type & fill slot:	Single Row Non-Fill Slot
r _{1,2} - min.	1.5 mm
Harmonized Tariff Code	8482.10.50.00
Manufacturer Item	1726308-2RS1

Number	
Basic dynamic load rating C	41 kN
Limiting speed ¹⁾	5000 r/min
operating temperature range:	-40 to +210 °F
Basic dynamic load rating - C	41 kN
Fatigue load limit P_u	1 kN
Calculation factor f_0	13
Fatigue load limit - P_u	1 kN
Calculation factor - f_0	13
Basic static load rating C_0	24 kN
Basic static load rating - C_0	24 kN