




Bearing No. W 638/8-2Z

D	16 mm
d	8 mm
B	6 mm
Bore	0.315 Inch 8 Millimeter
Noun	Bearing
UNSPSC	31171504
Category	Single Row Ball Bearing
Inventory	0.0
Enclosure	2 Metal Shields
Size (mm)	16x8x6
Snap Ring	No
Width (mm)	6
Mass bearing	0.0046 kg
Weight / LBS	0.009
Inch - Metric	Metric
Cage Material	Stainless Steel
D ₂	14.2 mm
d ₂	9.65 mm
Product Group	B00308
Other Features	Deep Groove
Keyword String	Ball
Bearing number	W 638/8-2Z
Limiting speed	45000 r/min
Rolling Element	Ball Bearing
Reference speed	90000 r/min
Precision Class	ABEC 1 ISO P0
Outside Diameter	0.63 Inch 16 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Manufacturer URL	http://www.skf.com
Long Description	8MM Bore; 16MM

	Outside Diameter; 6MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Stainl
Outer Race Width	0.236 Inch 6 Millimeter
Weight / Kilogram	0.004
Manufacturer Name	SKF
D _a max.	14.4 mm
Bore Diameter (mm)	16
d _a max.	9.6 mm
Internal Clearance	C0-Medium
r _a max.	0.2 mm
d _a min.	9.5 mm
Outer Diameter (mm)	8
r _a - max.	0.2 mm
D _a - max.	14.4 mm
d _a - min.	9.5 mm
Minimum Buy Quantity	N/A
r _{1,2} min.	0.2 mm
d _a - max.	9.6 mm
D ₂ ?	14.2 mm
d ₂ ?	9.65 mm
r _{1,2} - min.	0.2 mm
Harmonized Tariff Code	8482.10.50.68
Internal Special Features	No
Basic dynamic load rating C	0.715 kN
Basic dynamic load rating - C	0.715 kN
Maximum Capacity /	No

Filling Slot	
Fatigue load limit P_u	0.012 kN
Calculation factor k_r	0.02
Calculation factor f_0	7.5
Calculation factor - k_r	0.02
Fatigue load limit - P_u	0.012 kN
Calculation factor - f_0	7.5
Basic static load rating C_0	0.3 kN
Basic static load rating - C_0	0.3 kN