



Bearing No. 29396E

| | |
|---------------------|------------------|
| C | 72 mm |
| B | 51 mm |
| d | 480 mm |
| D | 730 mm |
| T | 150 mm |
| A | 270 mm |
| B1 | 51 mm |
| D1 | 590 mm |
| d1 | 705 mm |
| B2 | 144 mm |
| Width | 150 mm |
| r min. | 6 mm |
| Weight | 224 Kg |
| da min. | 595 mm |
| Da max. | 650 mm |
| ra max. | 5 mm |
| da (min) | 595 mm |
| Da (max) | 650 mm |
| ra (max) | 5 mm |
| Bore Type | Cylindrical Bore |
| Enclosure | Open |
| Bore Size | 480 mm |
| Size (mm) | 480x730x150 |
| Width (mm) | 150 |
| Configuration | Single Row |
| Bearing number | 29396E |
| Outside Diameter | 730 mm |
| Static Load Rating | 21,900,000 N |
| Bore Diameter (mm) | 480 |
| Dynamic Load Rating | 4,630,000 N |

| | |
|-------------------------------|----------|
| Outer Diameter (mm) | 730 |
| Limiting Speed - Oil | 410 rpm |
| Fillet Radius/Chamfer | 6 mm |
| Basic dynamic load rating (C) | 4630 kN |
| Basic static load rating (C0) | 21900 kN |