



Bearing No. 14130/14274

e	0.38
d	33,338 mm
D	69,012 mm
T	19,845 mm
B	19,583 mm
C	15,875 mm
a	15,3 mm
Da	59 mm
B_	19.583
Db	63 mm
da	45 mm
Y0	0.86
db	38,5 mm
C0	56
D_	69.012
Z_	17
C_	15.875
Y1	1.6
DE_	58.023
SLR	13.3
D_a	59
DI_	43.632
DA1	7.767
DA2	6.939
CUP	0.132
DA_	7.355
D_b	63
RAr	124.211
SDM_	50.856
KBRG	3161

yobi	14130/14274
CONE	0.207
ALP21	28
ALP22	34
ALP23	0
BETA_	1
BET21	3
BET23	0
BET22	35
r min.	3,5 mm
LangID	1
Weight	0,339 Kg
ALPHA_	14.283
r1 min.	3,3 mm
ra max.	3,5 mm
Oil rpm	7500
outer r	3.3
hidYobi	14130/14274
GRS rpm	5600
inner r	3.5
hidTable	ecat_NSTPRI
inner ra	3.5
outer rb	3.3
ra1 max.	3,3 mm
Size (mm)	33.338x69.012x19.845
SHOG_yobi	14130R/14274R
Prod_Type3	TRBSR_ID_A
Width (mm)	19,845
Bearing number	14130/14274
Bore Diameter (mm)	33,338
Outer Diameter (mm)	69,012
Calculation factor (e)	0,38

(Oil) Lubrication Speed	7500 r/min
Calculation factor (Y0)	0,86
(Grease) Lubrication Speed	5600 r/min
Basic static load rating (C0)	56 kN
Basic dynamic load rating (C)	47 kN