



Bearing No. W 6306-2Z

D	72 mm
d	30 mm
B	19 mm
Bore	1.181 Inch 30 Millimeter
Noun	Bearing
UNSPSC	31171504
Category	Single Row Ball Bearing
Inventory	0.0
Enclosure	2 Metal Shields
Size (mm)	72x30x19
Snap Ring	No
Width (mm)	19
Mass bearing	0.34 kg
Weight / LBS	0.7716
Inch - Metric	Metric
Cage Material	Stainless Steel
D ₂	62.35 mm
d ₁	44.9 mm
Product Group	B00308
Other Features	Deep Groove
Keyword String	Ball
Bearing number	W 6306-2Z
Limiting speed	11000 r/min
Rolling Element	Ball Bearing
Reference speed	22000 r/min
Precision Class	ABEC 1 ISO P0
Long Description	30MM Bore; 72MM Outside Diameter; 19MM Outer Race Width; 2 Metal Shields;

	Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Stai
Outside Diameter	2.835 Inch 72 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Manufacturer URL	http://www.skf.com
Outer Race Width	0.748 Inch 19 Millimeter
Manufacturer Name	SKF
Weight / Kilogram	0
D _a max.	65.5 mm
r _a max.	1 mm
d _a max.	44.5 mm
Internal Clearance	C0-Medium
Bore Diameter (mm)	72
d _a min.	36.5 mm
Outer Diameter (mm)	30
r _a - max.	1 mm
D _a - max.	65.5 mm
d _a - min.	36.5 mm
r _{1,2} min.	1.1 mm
Minimum Buy Quantity	N/A
d _a - max.	44.5 mm
D ₂ ?	62.35 mm
d ₁ ?	44.9 mm
r _{1,2} - min.	1.1 mm
Harmonized Tariff Code	8482.10.50.68
Internal Special Features	No
Basic dynamic load rating C	22.9 kN

Basic dynamic load rating - C	22.9 kN
Maximum Capacity / Filling Slot	No
Fatigue load limit P_u	0.64 kN
Calculation factor k_r	0.035
Calculation factor f_0	13.3
Calculation factor - k_r	0.035
Fatigue load limit - P_u	0.64 kN
Calculation factor - f_0	13.3
Basic static load rating C_0	15 kN
Basic static load rating - C_0	15 kN