



Bearing No. 2212-K-TVH-C3 + H312

	H312 / Adapter sleeve
d	60 mm
m	1,03 kg / Weight
e	0,23
D	110 mm
B	28 mm
l	47 mm
c	13 mm
Size (mm)	55x110x28
Width (mm)	28
m <sub>1</sub>	0,4 kg / Weight, adapter sleeve
Y <sub>1</sub>	2,69
d <sub>1</sub>	76,6 mm
Y <sub>2</sub>	4,16
D <sub>m</sub>	80 mm
C <sub>r</sub>	48000 N / Dynamic load rating (radial)
D <sub>1</sub>	98,8 mm
Y <sub>0</sub>	2,82
n <sub>G</sub>	6300 1/min / Limiting speed
n <sub>B</sub>	7100 1/min / Reference speed
C <sub>0r</sub>	16300 N / Static load rating (radial)
Bearing number	2212-K-TVH-C3 + H312
C <sub>ur</sub>	1020 N / Fatigue limit load, radial
d <sub>1H</sub>	55 mm
r <sub>a max</sub>	1,5 mm

$d_{b \text{ min}}$	65 mm
$D_{a \text{ max}}$	101 mm
$B_{a \text{ min}}$	8 mm
$d_{a \text{ max}}$	69 mm
Bore Diameter (mm)	55
Outer Diameter (mm)	110