




Bearing No. W 628-2Z

D	24 mm
d	8 mm
B	8 mm
Bore	0.315 Inch 8 Millimeter
Noun	Bearing
UNSPSC	31171504
Category	Single Row Ball Bearing
Inventory	0.0
Enclosure	2 Metal Shields
Size (mm)	24x8x8
Snap Ring	No
Width (mm)	8
Mass bearing	0.017 kg
Weight / LBS	0.0375
Inch - Metric	Metric
Cage Material	Stainless Steel
D ₂	19.9 mm
d ₂	11.9 mm
Product Group	B00308
Other Features	Deep Groove
Keyword String	Ball
Bearing number	W 628-2Z
Limiting speed	36000 r/min
Rolling Element	Ball Bearing
Reference speed	70000 r/min
Precision Class	ABEC 1 ISO P0
Inner Race Width	0 Inch 0 Millimeter
Outer Race Width	0.315 Inch 8 Millimeter
Manufacturer URL	http://www.skf.com
Long Description	8MM Bore; 24MM

	Outside Diameter; 8MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Stainl
Outside Diameter	0.945 Inch 24 Millimeter
Manufacturer Name	SKF
Weight / Kilogram	0
D _a max.	22 mm
Bore Diameter (mm)	24
d _a max.	11.8 mm
Internal Clearance	C0-Medium
r _a max.	0.3 mm
d _a min.	10 mm
Outer Diameter (mm)	8
r _a - max.	0.3 mm
D _a - max.	22 mm
d _a - min.	10 mm
Minimum Buy Quantity	N/A
r _{1,2} min.	0.3 mm
d _a - max.	11.8 mm
D ₂ ?	19.9 mm
d ₂ ?	11.9 mm
r _{1,2} - min.	0.3 mm
Harmonized Tariff Code	8482.10.50.68
Internal Special Features	No
Basic dynamic load rating C	2.47 kN
Basic dynamic load rating - C	2.5 kN

Maximum Capacity / Filling Slot	No
Fatigue load limit P_u	0.048 kN
Calculation factor k_r	0.03
Calculation factor f_0	10.2
Calculation factor - k_r	0.03
Fatigue load limit - P_u	0.048 kN
Calculation factor - f_0	10.2
Basic static load rating C_0	1.12 kN
Basic static load rating - C_0	1.1 kN