

Bearing No. W 628/6 R-2Z

D	13 mm
d	6 mm
B	5 mm
C	1,1 mm
D3	15 mm
Bore	0.236 Inch 6 Millimeter
Noun	Bearing
Weight	0,0029 Kg
UNSPSC	31171504
Category	Single Row Ball Bearing
Inventory	0.0
Size (mm)	6x13x5
Enclosure	2 Metal Shields
Snap Ring	No
Width (mm)	5
Mass bearing	0.0029 kg
Weight / LBS	0.011
Inch - Metric	Metric
Product Group	B00308
D ₃	15 mm
Cage Material	Stainless Steel
Keyword String	Ball
Other Features	Deep Groove Flanged Outer Ring Polymer Ball Bearing
Limiting speed	53000 r/min
Bearing number	W 628/6 R-2Z
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
Reference speed	110 000 r/min
Outside Diameter	0.512 Inch 13

	Millimeter
Long Description	6MM Bore; 13MM Outside Diameter; 5MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Stainl
Manufacturer URL	http://www.skf.com
Inner Race Width	0 Inch 0 Millimeter
Outer Race Width	0.197 Inch 5 Millimeter
Weight / Kilogram	0
Manufacturer Name	SKF
Bore Diameter (mm)	6
r_a max.	0.15 mm
d_a max.	7.3 mm
d_a min.	7.2 mm
Internal Clearance	C0-Medium
Outer Diameter (mm)	13
$r_{1,2}$ min.	0.15 mm
Minimum Buy Quantity	N/A
d_2 ?	7.4 mm
D_2 ?	11.7 mm
Harmonized Tariff Code	8482.10.50.68
Fatigue load limit (Pu)	0,01
Manufacturer Item Number	W 628/6 R-2Z
Internal Special Features	No
Basic dynamic load rating C	0.618 kN
Basic static load rating (C0)	0,224 kN

Basic dynamic load rating (C)	0,618 kN
Maximum Capacity / Filling Slot	No
Fatigue load limit P _u	0.01 kN
Calculation factor k _r	0.02
Calculation factor f ₀	7
Basic static load rating C ₀	0.224 kN