



**Bearing No. FYT 1.1/2 FM**

N	12 mm
d	38,1 mm
G	32,7 mm
H	143,7 mm
J	102 mm
L	14,3 mm
T	30,7 mm
A2	14 mm
Da	171,5 mm
s1	56,5 mm
A1	38,5 mm
B1	43,7 mm
Bore	1.5 Inch   38.1 Millimeter
Noun	Bearing
Seals	M Seal
UNSPSC	31171501
Weight	1,75 Kg
Category	Flange Block
Inventory	0.0
Bolt Spacing	5.656 Inch   143.67 Millimeter
Weight / LBS	4
Inch - Metric	Inch
Housing Style	2 Bolt Flange Block
Product Group	M06110
Other Features	Single Row   Standard Duty   Narrow Inner Race   Open End   Y Bearing
Keyword String	Flanged
Mounting Bolts	1/2 Inch

Relubricatable	Yes
Bearing number	FYT 1.1/2 FM
Mounting Method	Eccentric Collar
Rolling Element	Ball Bearing
Length Thru Bore	1.719 Inch   43.663 Millimeter
Long Description	2 Bolt Flange Block; 1-1/2" Bore; 5.7" Bolt Circle; 5-21/32" Bolt Spacing; 1 Piece Solid; Eccentric Collar Mount; Cast Iron; Ball Bearing; 1-23/32" Length Thru Bore; Relubricatable
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Housing Material	Cast Iron
Manufacturer Name	SKF
Weight / Kilogram	1.82
Bore Diameter (mm)	38,1
Insert Part Number	YET 208-108
Pilot Configuration	No Pilot
Minimum Buy Quantity	N/A
Cartridge Pilot Depth	0 Inch   0 Millimeter
Housing Configuration	1 Piece Solid
Harmonized Tariff Code	8483.20.40.40
Manufacturer Item Number	FYT 1.1/2 FM
Cartridge Pilot Diameter	0 Inch   0 Millimeter
Number of Mounting Holes	2
Expansion / Non-expansion	Non-expansion
Basic dynamic load rating (C)	19 kN
Basic static load rating (C0)	0,8 kN

Nominal Bolt Circle Diameter Round	5.7 Inch   144 Millimeter
------------------------------------	---------------------------