




Bearing No. FYT 1.7/16 FM

N	12 mm
d	36,513 mm
G	29,4 mm
H	130,2 mm
J	96 mm
L	14,3 mm
T	25,5 mm
A2	13 mm
Da	156 mm
s1	50,4 mm
A1	34,5 mm
B1	38,9 mm
Bore	1.438 Inch 36.525 Millimeter
Noun	Bearing
Seals	M Seal
UNSPSC	31171501
Weight	1,3 Kg
Category	Flange Block
Inventory	0.0
Bolt Spacing	5.125 Inch 130.18 Millimeter
Weight / LBS	2.9
Inch - Metric	Inch
Housing Style	2 Bolt Flange Block
Product Group	M06110
Other Features	Single Row Standard Duty Narrow Inner Race Open End Y Bearing
Keyword String	Flanged
Mounting Bolts	1/2 Inch

Relubricatable	Yes
Bearing number	FYT 1.7/16 FM
Mounting Method	Eccentric Collar
Rolling Element	Ball Bearing
Long Description	2 Bolt Flange Block; 1-7/16" Bore; 5.1" Bolt Circle; 5-1/8" Bolt Spacing; 1 Piece Solid; Eccentric Collar Mount; Cast Iron; Ball Bearing; 1-17/32" Length Thru Bore; Relubricatable;
Length Thru Bore	1.531 Inch 38.9 Millimeter
Housing Material	Cast Iron
Manufacturer URL	http://www.skf.com
Weight / Kilogram	1.32
Manufacturer Name	SKF
Insert Part Number	YET 207-107
Bore Diameter (mm)	36,513
Pilot Configuration	No Pilot
Minimum Buy Quantity	N/A
Housing Configuration	1 Piece Solid
Cartridge Pilot Depth	0 Inch 0 Millimeter
Harmonized Tariff Code	8483.20.40.40
Cartridge Pilot Diameter	0 Inch 0 Millimeter
Manufacturer Item Number	FYT 1.7/16 FM
Number of Mounting Holes	2
Expansion / Non- expansion	Non-expansion
Basic static load rating (C0)	0,655 kN
Basic dynamic load rating (C)	15,3 kN



Nominal Bolt Circle Diameter Round	5.1 Inch 130 Millimeter
---------------------------------------	---------------------------