




Bearing No. FYT 1/2 FM

N	10 mm
d	12,7 mm
G	22,1 mm
H	76,2 mm
J	54 mm
L	11,1 mm
T	9,56 mm
A2	11,5 mm
Da	98,5 mm
s1	36,8 mm
A1	23,4 mm
B1	26,6 mm
Bore	0.5 Inch 12.7 Millimeter
Noun	Bearing
Seals	M Seal
UNSPSC	31171501
Weight	0,35 Kg
Category	Flange Block
Inventory	0.0
Bolt Spacing	3 Inch 76.2 Millimeter
Weight / LBS	0.8
Inch - Metric	Inch
Housing Style	2 Bolt Flange Block
Product Group	M06110
Other Features	Single Row Standard Duty Narrow Inner Race Open End Y Bearing
Keyword String	Flanged
Mounting Bolts	3/8 Inch
Relubricatable	Yes

Bearing number	FYT 1/2 FM
Mounting Method	Eccentric Collar
Rolling Element	Ball Bearing
Long Description	2 Bolt Flange Block; 1/2" Bore; 3" Bolt Circle; 3" Bolt Spacing; 1 Piece Solid; Eccentric Collar Mount; Cast Iron; Ball Bearing; 1-7/64" Length Thru Bore; Relubricatable; M Seal Se
Length Thru Bore	1.109 Inch 28.169 Millimeter
Manufacturer URL	http://www.skf.com
Housing Material	Cast Iron
Weight / Kilogram	0.36
Manufacturer Name	SKF
Insert Part Number	YET 203-008
Bore Diameter (mm)	12,7
Pilot Configuration	No Pilot
Minimum Buy Quantity	N/A
Cartridge Pilot Depth	0 Inch 0 Millimeter
Housing Configuration	1 Piece Solid
Harmonized Tariff Code	8483.20.40.40
Manufacturer Item Number	FYT 1/2 FM
Cartridge Pilot Diameter	0 Inch 0 Millimeter
Number of Mounting Holes	2
Expansion / Non-expansion	Non-expansion
Basic static load rating (C0)	0,2 kN
Basic dynamic load rating (C)	4,75 kN



Nominal Bolt Circle Diameter Round	3 Inch 76 Millimeter
---------------------------------------	------------------------