




Bearing No. S7216 ACD/P4A

D	140 mm
d	80 mm
B	26 mm
a	38.8 mm
Ball - z	17
Size (mm)	140x80x26
Width (mm)	26
Mass bearing	1.51 kg
D ₂	124.3 mm
d ₂	99.5 mm
d ₁	99.5 mm
d ₂	99.5 mm
D ₂	124.3 mm
d ₁	99.5 mm
Bearing number	S7216 ACD/P4A
Preload class B	303 N/micron
Preload class A	257 N/micron
Preload class D	540 N/micron
Preload class C	401 N/micron
Number of balls z	17
r _b max.	1 mm
r _a max.	2 mm
D _b max.	134.4 mm
D _a max.	129 mm
d _b max.	98.5 mm
d _b min.	91 mm
d _a max.	98.5 mm
Bore Diameter (mm)	140
d _a min.	91 mm
Outer Diameter (mm)	80

d_a - max.	98.5 mm
d_a - min.	91 mm
Calculation factor e	0.68
Calculation factor f	1.09
d_b - max.	98.5 mm
D_b - max.	134.4 mm
r_a - max.	2 mm
r_b - max.	1 mm
d_b - min.	91 mm
$r_{3,4}$ min.	1 mm
$r_{1,2}$ min.	2 mm
Ball - D_w	17.462 mm
D_a - max.	129 mm
$r_{3,4}$ - min.	1 mm
$r_{1,2}$ - min.	2 mm
Calculation factor - f	1.09
Calculation factor - e	0.68
Ball diameter D_w	17.462 mm
Basic dynamic load rating C	81.9 kN
Preload class A G_A	520 N
Basic dynamic load rating - C	81.9 kN
Preload class B G_B	1040 N
Preload class C G_C	2080 N
Preload class D G_D	4160 N
Preload class B - G_B	1040 N
Preload class C - G_C	2080 N
Preload class A - G_A	520 N
Preload class D - G_D	4160 N
Calculation factor f_1	0.99
Fatigue load limit P_u	2.9 kN

Calculation factor f_{2A}	1
Calculation factor f_{2B}	1.01
Calculation factor f_{2C}	1.02
Calculation factor f_{2D}	1.05
Calculation factor f_{HC}	1
Calculation factor - X_2	0.67
Calculation factor - Y_1	0.92
Calculation factor - Y_2	1.41
Fatigue load limit - P_u	2.9 kN
Calculation factor - Y_0	0.76
Calculation factor - f_1	0.99
Calculation factor - f_{HC}	1
Calculation factor - f_{2D}	1.05
Calculation factor - f_{2C}	1.02
Calculation factor - f_{2B}	1.01
Calculation factor - f_{2A}	1
Limiting speed for grease lubrication	8500 r/min
Basic static load rating C_0	72 kN
Static axial stiffness, preload class D	540 N/ μ m
Attainable speed for grease lubrication	8500 r/min
Static axial stiffness, preload class C	401 N/ μ m
Static axial stiffness, preload class B	303 N/ μ m
Static axial stiffness, preload class A	257 N/ μ m
Basic static load rating - C_0	72 kN

Calculation factor (single, tandem) Y_2	0.87
Calculation factor (single, tandem) Y_0	0.38
Calculation factor (single, tandem) X_2	0.41
Calculation factor (back- to-back, face-to-face) Y_1	0.92
Calculation factor (back- to-back, face-to-face) Y_2	1.41
Calculation factor (back- to-back, face-to-face) Y_0	0.76
Calculation factor (back- to-back, face-to-face) X_2	0.67