




Bearing No. NJ 313 ECJ

F	82.5 mm
s	2.2 mm
d	65 mm
D	140 mm
B	33 mm
Bore	2.559 Inch 65 Millimeter
Noun	Bearing
Width	1.299 Inch 33 Millimeter
UNSPSC	31171547
s max.	2.2 mm
series:	NJ3
Profile	Complete with Outer and Inner Ring
flanges:	(2) Outer Ring, (1) Inner Ring
Category	Cylindrical Roller Bearing
Retainer	Yes
Size (mm)	140x65x33
Snap Ring	No
Separable	Inner Ring - One Side
Inventory	0.0
bore type:	Straight
Width (mm)	33
maximum rpm:	6000 RPM
Weight / LBS	5.225
Bore Profile	Straight
Mass bearing	2.32 kg
closure type:	Open
Product Group	B04144

d ₁	90.5 mm
Cage Material	Steel
D ₁	117.4 mm
Inch - Metric	Metric
Bearing number	NJ 313 ECJ
Relubricatable	Yes
fillet radius:	2 mm
cage material:	Steel
Limiting speed	6000 r/min
bore diameter:	65 mm
Other Features	High Capacity 1 Rib Inner Ring 2 Rib Outer Ring Cage on Outer Ring ID
overall width:	33 mm
finish/coating:	Uncoated
number of rows:	1
Reference speed	5300 r/min
Precision Class	RBEC 1 ISO P0
Rolling Element	Cylindrical Roller Bearing
Long Description	65MM Bore; Straight Bore Profile; 140MM Outside Diameter; 33MM Width; Steel Cage Material; RBEC 1 ISO P0; Single Row; Inner Ring - One Side Separable; No Snap Ring; Relubricatable; C0-Medium Intern
Limiting value e	0.2
ring separation:	Separable Ring
Outside Diameter	5.512 Inch 140 Millimeter
Manufacturer URL	http://www.skf.com

bearing material:	Steel
Manufacturer Name	SKF
outer ring width:	33 mm
outside diameter:	140 mm
precision rating:	Not Rated
Weight / Kilogram	2.372
d _a min.	77 mm
d _a max.	80 mm
d _b min.	93 mm
r _a max.	2 mm
D _a max.	127.8 mm
Bore Diameter (mm)	140
Internal Clearance	C0-Medium
Axial load factor Y	0.6
internal clearance:	C0
Outer Diameter (mm)	65
r _{1,2} min.	2.1 mm
r _{3,4} min.	2.1 mm
r _a - max.	2 mm
Minimum Buy Quantity	N/A
D _a - max.	127.8 mm
d _a - min.	77 mm
d _b - min.	93 mm
d _a - max.	80 mm
static load capacity:	196 kN
d ₁ ?	90.5 mm
D ₁ ?	117.4 mm
Harmonized Tariff Code	8482.50.00.00
r _{1,2} - min.	2.1 mm
dynamic load capacity:	212 kN
r _{3,4} - min.	2.1 mm
Manufacturer Item Number	NJ 313 ECJ

Number of Rows of Rollers	Single Row
Basic dynamic load rating C	212 kN
operating temperature range:	Maximum of +300 °F
Basic dynamic load rating - C	212 kN
Fatigue load limit P_u	25.5 kN
Calculation factor k_r	0.15
Fatigue load limit - P_u	25.5 kN
Calculation factor - k_r	0.15
Basic static load rating C_0	196 kN
Basic static load rating - C_0	196 kN