




Bearing No. NJ 2312 ECP

F	77 mm
s	3.6 mm
d	60 mm
D	130 mm
B	46 mm
Bore	2.362 Inch 60 Millimeter
Noun	Bearing
Width	1.811 Inch 46 Millimeter
s max.	3.6 mm
UNSPSC	31171547
Profile	Complete with Outer and Inner Ring
series:	NJ23
flanges:	(2) Outer Ring, (1) Inner Ring
Retainer	Yes
Category	Cylindrical Roller Bearing
Separable	Inner Ring - One Side
Size (mm)	130x60x46
Inventory	0.0
Snap Ring	No
Width (mm)	46
bore type:	Straight
Bore Profile	Straight
Mass bearing	2.81 kg
Weight / LBS	6.31
application:	Piston Type Machines, Rolling Mills, Spindles/Machine Tools

maximum rpm:	6700 RPM
closure type:	Open
Product Group	B04144
Cage Material	Polymer
Inch - Metric	Metric
D ₁	108.5 mm
d ₁	84.3 mm
bore diameter:	60 mm
overall width:	46 mm
cage material:	Polyamide
Other Features	High Capacity 1 Rib Inner Ring 2 Rib Outer Ring Cage on Outer Ring ID
fillet radius:	2 mm
Relubricatable	Yes
Bearing number	NJ 2312 ECP
Limiting speed	6700 r/min
Rolling Element	Cylindrical Roller Bearing
Precision Class	RBEC 1 ISO P0
number of rows:	1
finish/coating:	Uncoated
Reference speed	5600 r/min
Manufacturer URL	http://www.skf.com
Outside Diameter	5.118 Inch 130 Millimeter
Long Description	60MM Bore; Straight Bore Profile; 130MM Outside Diameter; 46MM Width; Polymer Cage Material; RBEC 1 ISO P0; Single Row; Inner Ring - One Side Separable; No Snap Ring; Relubricatable;

	C0-Medium Inte
Limiting value e	0.3
ring separation:	Separable Ring
precision rating:	RBEC 1 (ISO Class Normal)
bearing material:	Steel
outer ring width:	46 mm
Weight / Kilogram	2.865
Manufacturer Name	SKF
outside diameter:	130 mm
Bore Diameter (mm)	130
Internal Clearance	C0-Medium
d _a min.	72 mm
d _a max.	74 mm
D _a max.	118.1 mm
r _a max.	2 mm
d _b min.	87 mm
Outer Diameter (mm)	60
Axial load factor Y	0.4
internal clearance:	C0
r _{3,4} min.	2.1 mm
r _{1,2} min.	2.1 mm
d _a - min.	72 mm
D _a - max.	118.1 mm
Minimum Buy Quantity	N/A
r _a - max.	2 mm
d _a - max.	74 mm
d _b - min.	87 mm
static load capacity:	265 kN
d ₁ ?	84.3 mm
D ₁ ?	108.5 mm
r _{3,4} - min.	2.1 mm
Harmonized Tariff Code	8482.50.00.00

$r_{1,2}$ - min.	2.1 mm
dynamic load capacity:	260 kN
Manufacturer Item Number	NJ 2312 ECP
Number of Rows of Rollers	Single Row
Basic dynamic load rating C	260 kN
operating temperature range:	Maximum of +300 °F
Basic dynamic load rating - C	260 kN
Fatigue load limit P_u	34.5 kN
Calculation factor k_r	0.25
Fatigue load limit - P_u	34.5 kN
Calculation factor - k_r	0.25
Basic static load rating C_0	265 kN
Basic static load rating - C_0	265 kN