




Bearing No. 22218 E

b	6 mm
K	3 mm
d	90 mm
D	160 mm
B	40 mm
Noun	Bearing
Bore	3.543 Inch 90 Millimeter
Width	1.575 Inch 40 Millimeter
UNSPSC	31171510
series:	222
Category	Spherical Roller Bearing
Size (mm)	160x90x40
Enclosure	Open
Inventory	0.0
bore type:	Straight
Width (mm)	40
cage type:	Inner Ring Guided
maximum rpm:	5300 RPM
Weight / LBS	7.621
Bore Profile	Straight
Mass bearing	3.4 kg
D ₁	141 mm
Cage Material	Steel
closure type:	Open
d ₂	106 mm
Product Group	B04311
Inch - Metric	Metric
fillet radius:	2 mm

cage material:	Steel
overall width:	4.3800 in
bore diameter:	90 mm
Keyword String	Spherical
Withdrawal Nut	Not Applicable
Relubricatable	Yes
Bearing number	22218 E
Limiting speed	5300 r/min
finish/coating:	Uncoated
Rolling Element	Spherical Roller Bearing
Mounting Method	Shaft Mount
Reference speed	3800 r/min
outer ring type:	Not Split
Manufacturer URL	http://www.skf.com
Outside Diameter	6.299 Inch 160 Millimeter
Long Description	90MM Straight Bore; 160MM Outside Diameter; 40MM Width; C0-Medium Clearance; Shaft Mount; Double Row of Spherical Roller Bearings; Steel Cage Material; Open Enclosure; Relubricatable
outside diameter:	160 mm
Weight / Kilogram	3.46
precision rating:	Not Rated
bearing material:	Steel
Withdrawal Sleeve	Not Applicable
outer ring width:	40 mm
Manufacturer Name	SKF
D _a max.	149 mm
Bore Diameter (mm)	160

Internal Clearance	C0-Medium
r_a max.	2 mm
d_a min.	101 mm
Adapter Part Number	Not Applicable Inch Not Applicable Millimeter
Outer Diameter (mm)	90
internal clearance:	C0
$r_{1,2}$ min.	2 mm
Minimum Buy Quantity	N/A
d_a - min.	101 mm
D_a - max.	149 mm
r_a - max.	2 mm
Calculation factor e	0.24
D_1 ?	141 mm
d_2 ?	106 mm
static load capacity:	375 kN
Calculation factor - e	0.24
dynamic load capacity:	325 kN
$r_{1,2}$ - min.	2 mm
lubrication hole type:	Lubrication Groove & Hole
Harmonized Tariff Code	84823080
Number of Rows of Rollers	Double Row
Basic dynamic load rating C	331 kN
operating temperature range:	Maximum of +390 °F
Basic dynamic load rating - C	331 kN
Calculation factor Y_1	2.8
Fatigue load limit P_u	39 kN
Calculation factor Y_2	4.2
Calculation factor Y_0	2.8

Calculation factor - Y_1	2.8
Calculation factor - Y_2	4.2
Calculation factor - Y_0	2.8
Fatigue load limit - P_u	39 kN
Basic static load rating C_0	375 kN
Basic static load rating - C_0	375 kN