




Bearing No. NJ 2222 ECP

F	132.5 mm
s	3.7 mm
d	110 mm
D	200 mm
B	53 mm
Bore	4.331 Inch 110 Millimeter
Noun	Bearing
Width	2.087 Inch 53 Millimeter
s max.	3.7 mm
UNSPSC	31171547
Profile	Complete with Outer and Inner Ring
series:	NJ22
flanges:	(2) Outer Ring, (1) Inner Ring
Retainer	Yes
Category	Cylindrical Roller Bearing
Separable	Inner Ring - One Side
Size (mm)	200x110x53
Inventory	0.0
Snap Ring	No
Width (mm)	53
bore type:	Straight
Bore Profile	Straight
Mass bearing	6.72 kg
Weight / LBS	15.014
application:	Piston Type Machines, Rolling Mills, Spindles/Machine Tools

maximum rpm:	4000 RPM
closure type:	Open
Product Group	B04144
Cage Material	Polymer
Inch - Metric	Metric
D ₁	172.5 mm
d ₁	141 mm
bore diameter:	110 mm
overall width:	53 mm
cage material:	Polyamide
Other Features	High Capacity 1 Rib Inner Ring 2 Rib Outer Ring Cage on Outer Ring ID
fillet radius:	2 mm
Relubricatable	Yes
Bearing number	NJ 2222 ECP
Limiting speed	4000 r/min
Rolling Element	Cylindrical Roller Bearing
Precision Class	RBEC 1 ISO P0
number of rows:	1
finish/coating:	Uncoated
Reference speed	3600 r/min
Outside Diameter	7.874 Inch 200 Millimeter
ring separation:	Separable Ring
Long Description	110MM Bore; Straight Bore Profile; 200MM Outside Diameter; 53MM Width; Polymer Cage Matetrial; RBEC 1 ISO P0; Single Row; Inner Ring - One Side Separable; No Snap Ring; Relubricatable;

	C0-Medium Int
Limiting value e	0.3
Manufacturer URL	http://www.skf.com
bearing material:	Steel
outside diameter:	200 mm
precision rating:	RBEC 1 (ISO Class Normal)
outer ring width:	53 mm
Weight / Kilogram	6.816
Manufacturer Name	SKF
d _a max.	129 mm
d _b min.	144 mm
D _a max.	187 mm
d _a min.	122 mm
Bore Diameter (mm)	200
r _a max.	2 mm
Internal Clearance	C0-Medium
Outer Diameter (mm)	110
Axial load factor Y	0.4
internal clearance:	C0
r _{3,4} min.	2.1 mm
r _{1,2} min.	2.1 mm
d _a - min.	122 mm
D _a - max.	187 mm
Minimum Buy Quantity	N/A
r _a - max.	2 mm
d _a - max.	129 mm
d _b - min.	144 mm
static load capacity:	520 kN
d ₁ ?	141 mm
D ₁ ?	172.5 mm
r _{3,4} - min.	2.1 mm
Harmonized Tariff Code	8482.50.00.00

$r_{1,2}$ - min.	2.1 mm
dynamic load capacity:	440 kN
Manufacturer Item Number	NJ 2222 ECP
Number of Rows of Rollers	Single Row
Basic dynamic load rating C	440 kN
operating temperature range:	Maximum of +300 °F
Basic dynamic load rating - C	440 kN
Fatigue load limit P_u	61 kN
Calculation factor k_r	0.2
Fatigue load limit - P_u	61 kN
Calculation factor - k_r	0.2
Basic static load rating C_0	520 kN
Basic static load rating - C_0	520 kN