



Bearing No. 15578/15520

e	0.35
d	25,4 mm
D	57,15 mm
T	17,462 mm
B	17,462 mm
C	13,495 mm
a	12,4 mm
Da	51 mm
B_	17.462
Db	53 mm
da	32,5 mm
Y0	0.95
db	30,5 mm
C0	45.5
D_	57.15
Z_	17
C_	13.495
Y1	1.7
DE_	49.111
SLR	12.2
D_a	51
DI_	35.977
DA1	7.036
DA2	6.294
CUP	0.07
DA_	6.667
D_b	53
RAr	115.199
SDM_	42.568
KBRG	3161

yobi	15578/15520
CONE	0.151
ALP21	26
ALP22	0
ALP23	0
BETA_	1
BET21	3
BET23	0
BET22	30
r min.	1,3 mm
LangID	1
Weight	0,221 Kg
ALPHA_	13
r1 min.	1,5 mm
ra max.	1,3 mm
Oil rpm	9000
outer r	1.5
hidYobi	15578/15520
GRS rpm	6700
inner r	1.3
hidTable	ecat_NSTPRI
inner ra	1.3
outer rb	1.5
ra1 max.	1,5 mm
Size (mm)	25.4x57.15x17.462
SHOG_yobi	15578R/15520R
Prod_Type3	TRBSR_ID_A
Width (mm)	17,462
Bearing number	15578/15520
Bore Diameter (mm)	25,4
Outer Diameter (mm)	57,15
Calculation factor (e)	0,35

(Oil) Lubrication Speed	9000 r/min
Calculation factor (Y0)	0,95
(Grease) Lubrication Speed	6700 r/min
Basic static load rating (C0)	45,5 kN
Basic dynamic load rating (C)	39,5 kN