



Bearing No. 2207 EKTN9 + H 307

D	72 mm
d	30 mm
B	23 mm
Size (mm)	72x30x35
Width (mm)	35
d ₃	52 mm
B ₁	35 mm
d ₁	30 mm
B ₁	35 mm
d ₃	52 mm
D ₁	62.9 mm
B ₄	9 mm
B ₄	9 mm
Limiting speed	12000 r/min
Bearing number	2207 EKTN9 + H 307
Reference speed	18000 r/min
r _a max.	1.1 mm
B _a min.	5 mm
D _a max.	65 mm
d _b min.	39 mm
d _a max.	45 mm
Bore Diameter (mm)	72
Outer Diameter (mm)	30
B _a - min.	5 mm
r _a - max.	1.1 mm
d _b - min.	39 mm
d _a - max.	45 mm
r _{1,2} min.	1.1 mm
Calculation factor e	0.31

D _a - max.	65 mm
D ₁ ?	62.9 mm
Calculation factor - e	0.31
r _{1,2} - min.	1.1 mm
Fatigue load limit - P _u	0.46 kN
Basic dynamic load rating C	30.2 kN
Mass bearing + adapter sleeve	0.54 kg
Basic dynamic load rating - C	30.2 kN
Calculation factor k _r	0.045
Calculation factor Y ₂	3.1
Calculation factor Y ₁	2
Calculation factor Y ₀	2.2
Fatigue load limit P _u	0.455 kN
Calculation factor - Y ₂	3.1
Calculation factor - Y ₁	2
Calculation factor - k _r	0.045
Calculation factor - Y ₀	2.2
Permissible angular misalignment ?	2.5 °
Basic static load rating C ₀	8.8 kN
Basic static load rating - C ₀	8.8 kN