


Cylindrical bore



Tapered bore



### Bearing No. 2206ETN9

|                               |             |
|-------------------------------|-------------|
| D                             | 62 mm       |
| d                             | 30 mm       |
| B                             | 20 mm       |
| C                             | 20 mm       |
| d2                            | 38,8 mm     |
| D1                            | 55 mm       |
| Weight                        | 0,26 Kg     |
| da min.                       | 35,6 mm     |
| ra max.                       | 1 mm        |
| r1 min.                       | 1 mm        |
| r2 min.                       | 1 mm        |
| Da max.                       | 56,4 mm     |
| Size (mm)                     | 30x62x20    |
| Width (mm)                    | 20          |
| Limiting speed                | 15000 r/min |
| Bearing number                | 2206ETN9    |
| Reference speed               | 22000 r/min |
| Bore Diameter (mm)            | 30          |
| Outer Diameter (mm)           | 62          |
| Calculation factor (e)        | 0,33        |
| Fatigue load limit (Pu)       | 0,35        |
| Calculation factor (kr)       | 0,045       |
| Calculation factor (Y0)       | 2           |
| Calculation factor (Y1)       | 1,9         |
| Basic dynamic load rating (C) | 23,8 kN     |
| Basic static load rating (C0) | 6,7 kN      |