




Bearing No. NJ 219 ECP

F	112.5 mm
s	1.7 mm
d	95 mm
D	170 mm
B	32 mm
Bore	3.74 Inch 95 Millimeter
Noun	Bearing
Width	1.26 Inch 32 Millimeter
s max.	1.7 mm
UNSPSC	31171547
Profile	Complete with Outer and Inner Ring
series:	NJ2
flanges:	(2) Outer Ring, (1) Inner Ring
Retainer	Yes
Category	Cylindrical Roller Bearing
Separable	Inner Ring - One Side
Size (mm)	170x95x32
Inventory	0.0
Snap Ring	No
Width (mm)	32
bore type:	Straight
Bore Profile	Straight
Mass bearing	2.92 kg
Weight / LBS	6.57
application:	Piston Type Machines, Rolling Mills, Spindles/Machine Tools
maximum rpm:	4800 RPM
closure type:	Open

Product Group	B04144
Cage Material	Polymer
Inch - Metric	Metric
D ₁	147.4 mm
d ₁	120 mm
bore diameter:	95 mm
overall width:	32 mm
cage material:	Polyamide
Other Features	High Capacity 1 Rib Inner Ring 2 Rib Outer Ring Cage on Outer Ring ID
fillet radius:	2 mm
Relubricatable	Yes
Bearing number	NJ 219 ECP
Limiting speed	4800 r/min
Rolling Element	Cylindrical Roller Bearing
Precision Class	RBEC 1 ISO P0
number of rows:	1
finish/coating:	Uncoated
Reference speed	4300 r/min
Outside Diameter	6.693 Inch 170 Millimeter
ring separation:	Separable Ring
Long Description	95MM Bore; Straight Bore Profile; 170MM Outside Diameter; 32MM Width; Polymer Cage Matetrial; RBEC 1 ISO P0; Single Row; Inner Ring - One Side Separable; No Snap Ring; Relubricatable; C0-Medium Inte
Limiting value e	0.2

Manufacturer URL	http://www.skf.com
bearing material:	Steel
outside diameter:	170 mm
precision rating:	RBEC 1 (ISO Class Normal)
outer ring width:	32 mm
Weight / Kilogram	2.983
Manufacturer Name	SKF
d _a max.	110 mm
d _b min.	123 mm
D _a max.	157.8 mm
d _a min.	107 mm
Bore Diameter (mm)	170
r _a max.	2 mm
Internal Clearance	C0-Medium
Outer Diameter (mm)	95
Axial load factor Y	0.6
internal clearance:	C0
r _{3,4} min.	2.1 mm
r _{1,2} min.	2.1 mm
d _a - min.	107 mm
D _a - max.	157.8 mm
Minimum Buy Quantity	N/A
r _a - max.	2 mm
d _a - max.	110 mm
d _b - min.	123 mm
static load capacity:	265 kN
d ₁ ?	120 mm
D ₁ ?	147.4 mm
r _{3,4} - min.	2.1 mm
Harmonized Tariff Code	8482.50.00.00
r _{1,2} - min.	2.1 mm
dynamic load capacity:	255 kN

Manufacturer Item Number	NJ 219 ECP
Number of Rows of Rollers	Single Row
Basic dynamic load rating C	255 kN
operating temperature range:	Maximum of +300 °F
Basic dynamic load rating - C	255 kN
Fatigue load limit P_u	32.5 kN
Calculation factor k_r	0.15
Fatigue load limit - P_u	32.5 kN
Calculation factor - k_r	0.15
Basic static load rating C_0	265 kN
Basic static load rating - C_0	265 kN