




Bearing No. W 607-2RS1

D	19 mm
d	7 mm
B	6 mm
Bore	0.276 Inch 7 Millimeter
Noun	Bearing
UNSPSC	31171504
Category	Single Row Ball Bearing
Snap Ring	No
Size (mm)	19x7x6
Enclosure	2 Seals
Inventory	0.0
Width (mm)	6
Weight / LBS	0.02
Mass bearing	0.0072 kg
Product Group	B00308
d ₂	9 mm
D ₂	16.5 mm
Inch - Metric	Metric
Cage Material	Stainless Steel
Bearing number	W 607-2RS1
Keyword String	Ball
Enclosure Type	Contact Seal
Other Features	Deep Groove NBR Seal
Limiting speed	24000 r/min
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Manufacturer URL	http://www.skf.com
Long Description	7MM Bore; 19MM Outside Diameter; 6MM Outer Race Width; 2

	Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Stainless Steel
Outside Diameter	0.748 Inch 19 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Outer Race Width	0.236 Inch 6 Millimeter
Manufacturer Name	SKF
Weight / Kilogram	0.007
r _a max.	0.3 mm
Internal Clearance	C0-Medium
D _a max.	17 mm
d _a max.	8.9 mm
d _a min.	8.7 mm
Bore Diameter (mm)	19
Outer Diameter (mm)	7
r _a - max.	0.3 mm
r _{1,2} min.	0.3 mm
D _a - max.	17 mm
d _a - min.	8.7 mm
d _a - max.	8.9 mm
Minimum Buy Quantity	N/A
d ₂ ?	9 mm
D ₂ ?	16.5 mm
r _{1,2} - min.	0.3 mm
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	W 607-2RS1
Internal Special Features	No

Basic dynamic load rating C	1.53 kN
Basic dynamic load rating - C	1.5 kN
Maximum Capacity / Filling Slot	No
Fatigue load limit P_u	0.025 kN
Calculation factor k_r	0.03
Calculation factor f_0	7.9
Fatigue load limit - P_u	0.025 kN
Calculation factor - k_r	0.03
Calculation factor - f_0	7.9
Basic static load rating C_0	0.585 kN
Basic static load rating - C_0	0.585 kN