



Bearing No. 16150/16284

e	0.4
D	72,238 mm
C	15,875 mm
B	20,638 mm
T	20,638 mm
a	16 mm
d	38,1 mm
C_	15.875
C0	59.5
Z_	18
Da	63 mm
db	43 mm
Y1	1.5
da	49,5 mm
B_	20.638
D_	72.238
Y0	0.82
D_a	63
DE_	60.909
SLR	13.3
D_b	67
RAr	124.211
DI_	46.516
CUP	0.146
DA_	7.355
DA2	6.939
DA1	7.767
SDM_	53.724
yobi	16150/16284
KBRG	3161

CONE	0.212
ALP23	0
BETA_	1
BET21	3
ALP21	30
BET22	35
BET23	0
ALP22	0
ALPHA_	15
r min.	3,5 mm
LangID	1
Weight	0,358 Kg
hidYobi	16150/16284
Oil rpm	7100
inner r	3.5
ra max.	3,5 mm
outer r	1.3
GRS rpm	5300
r1 min.	1,3 mm
hidTable	ecat_NSTPRI
inner ra	3.5
outer rb	1.3
ra1 max.	1,3 mm
Size (mm)	38.1x72.238x20.638
SHOG_yobi	16150R/16284R
Prod_Type3	TRBSR_ID_A
Width (mm)	20,638
Bearing number	16150/16284
Bore Diameter (mm)	38,1
Outer Diameter (mm)	72,238
Calculation factor (e)	0,4
Calculation factor (Y0)	0,82

(Oil) Lubrication Speed	7100 r/min
(Grease) Lubrication Speed	5300 r/min
Basic dynamic load rating (C)	48,5 kN
Basic static load rating (C0)	59,5 kN