




Bearing No. 07098/07205

e	0.4
d	24,981 mm
D	52,001 mm
T	15,011 mm
B	14,26 mm
C	12,7 mm
a	12,1 mm
Da	44,5 mm
B_	14.26
Db	48 mm
da	31 mm
Y0	0.82
db	29 mm
C0	27.9
D_	52.001
Z_	16
C_	12.7
Y1	1.5
DE_	43.599
SLR	9.3
D_a	44.5
DI_	32.114
DA1	6.2
DA2	5.554
CUP	0.061
DA_	5.879
D_b	48
RAr	88.826
SDM_	37.871
KBRG	3161

yobi	07098/07205
CONE	0.085
ALP21	30
ALP22	0
ALP23	0
BETA_	2
BET21	4
BET23	0
BET22	0
r min.	1,5 mm
LangID	1
Weight	0,146 Kg
ALPHA_	15
r1 min.	2 mm
ra max.	1,5 mm
Oil rpm	10000
outer r	2
hidYobi	07098/07205
GRS rpm	7500
inner r	1.5
hidTable	ecat_NSTPRI
inner ra	1.5
outer rb	2
ra1 max.	2 mm
Size (mm)	24.981x52.001x15.011
SHOG_yobi	07098R/07205R
Prod_Type3	TRBSR_ID_A
Width (mm)	15,011
Bearing number	07098/07205
Bore Diameter (mm)	24,981
Outer Diameter (mm)	52,001
Calculation factor (e)	0,4

(Oil) Lubrication Speed	10000 r/min
Calculation factor (Y0)	0,82
(Grease) Lubrication Speed	7500 r/min
Basic static load rating (C0)	27,9 kN
Basic dynamic load rating (C)	26 kN