



Bearing No. 17098/17244

e	0.38
d	24,981 mm
D	62 mm
T	16,002 mm
B	16,566 mm
C	14,288 mm
a	12,8 mm
Da	54 mm
B_	16.566
Db	57 mm
da	33 mm
Y0	0.86
db	30,5 mm
C0	39.5
D_	62
Z_	15
C_	14.288
Y1	1.6
DE_	52.849
SLR	11
D_a	54
DI_	37.837
DA1	7.782
DA2	7.019
CUP	0.091
DA_	7.403
D_b	57
RAr	111.502
SDM_	45.133
KBRG	3161

yobi	17098/17244
CONE	0.165
ALP21	28
ALP22	35
ALP23	0
BETA_	2
BET21	4
BET23	0
BET22	0
r min.	1,5 mm
LangID	1
Weight	0,256 Kg
ALPHA_	14.292
r1 min.	1,5 mm
ra max.	1,5 mm
Oil rpm	8500
outer r	1.5
hidYobi	17098/17244
GRS rpm	6300
inner r	1.5
hidTable	ecat_NSTPRI
inner ra	1.5
outer rb	1.5
ra1 max.	1,5 mm
Size (mm)	24.981x62x16.002
SHOG_yobi	17098R/17244R
Prod_Type3	TRBSR_ID_A
Width (mm)	16,002
Bearing number	17098/17244
Bore Diameter (mm)	24,981
Outer Diameter (mm)	62
Calculation factor (e)	0,38

(Oil) Lubrication Speed	8500 r/min
Calculation factor (Y0)	0,86
(Grease) Lubrication Speed	6300 r/min
Basic static load rating (C0)	39,5 kN
Basic dynamic load rating (C)	37 kN