




Bearing No. W 6005-2RS1

D	47 mm
d	25 mm
B	12 mm
Bore	0.984 Inch 25 Millimeter
Noun	Bearing
UNSPSC	31171504
Category	Single Row Ball Bearing
Snap Ring	No
Size (mm)	47x25x12
Enclosure	2 Seals
Inventory	10.0
Width (mm)	12
Weight / LBS	0.182
Mass bearing	0.077 kg
Product Group	B00308
d ₁	31.7 mm
D ₂	42.7 mm
Inch - Metric	Metric
Cage Material	Stainless Steel
Bearing number	W 6005-2RS1
Keyword String	Ball
Enclosure Type	Contact Seal
Other Features	Deep Groove NBR Seal
Limiting speed	9500 r/min
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Manufacturer URL	http://www.skf.com
Long Description	25MM Bore; 47MM Outside Diameter;

	12MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Stainless St
Outer Race Width	0.472 Inch 12 Millimeter
Outside Diameter	1.85 Inch 47 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Manufacturer Name	SKF
Weight / Kilogram	0.075
r_a max.	0.6 mm
Internal Clearance	C0-Medium
D_a max.	44.5 mm
d_a max.	31.5 mm
d_a min.	29 mm
Bore Diameter (mm)	47
Outer Diameter (mm)	25
r_a - max.	0.6 mm
$r_{1,2}$ min.	0.6 mm
D_a - max.	44.5 mm
d_a - min.	29 mm
d_a - max.	31.5 mm
Minimum Buy Quantity	N/A
d_1 ?	31.7 mm
D_2 ?	42.73 mm
$r_{1,2}$ - min.	0.6 mm
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	W 6005-2RS1
Internal Special Features	No

Basic dynamic load rating C	8.71 kN
Basic dynamic load rating - C	10.1 kN
Maximum Capacity / Filling Slot	No
Fatigue load limit P_u	0.25 kN
Calculation factor k_r	0.03
Calculation factor f_0	14.5
Fatigue load limit - P_u	0.25 kN
Calculation factor - k_r	0.03
Calculation factor - f_0	14.5
Basic static load rating C_0	5.85 kN
Basic static load rating - C_0	5.8 kN