




Bearing No. W 6006-2RS1

D	55 mm
d	30 mm
B	13 mm
Bore	1.181 Inch 30 Millimeter
Noun	Bearing
UNSPSC	31171504
Category	Single Row Ball Bearing
Snap Ring	No
Size (mm)	55x30x13
Enclosure	2 Seals
Inventory	0.0
Width (mm)	13
Weight / LBS	0.25
Mass bearing	0.11 kg
Product Group	B00308
d ₁	38 mm
D ₂	49.9 mm
Inch - Metric	Metric
Cage Material	Stainless Steel
Bearing number	W 6006-2RS1
Keyword String	Ball
Enclosure Type	Contact Seal
Other Features	Deep Groove NBR Seal
Limiting speed	8000 r/min
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Manufacturer URL	http://www.skf.com
Long Description	30MM Bore; 55MM Outside Diameter;

	13MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Stainless St
Outside Diameter	2.165 Inch 55 Millimeter
Outer Race Width	0.512 Inch 13 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Manufacturer Name	SKF
Weight / Kilogram	0.11
r_a max.	1 mm
Internal Clearance	C0-Medium
D_a max.	50.5 mm
d_a max.	37.5 mm
d_a min.	35 mm
Bore Diameter (mm)	55
Outer Diameter (mm)	30
r_a - max.	1 mm
$r_{1,2}$ min.	1 mm
d_a - max.	37.5 mm
D_a - max.	50.5 mm
d_a - min.	35 mm
Minimum Buy Quantity	N/A
d_1 ?	38 mm
D_2 ?	49.95 mm
$r_{1,2}$ - min.	1 mm
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	W 6006-2RS1
Internal Special Features	No

Basic dynamic load rating C	11.4 kN
Basic dynamic load rating - C	11.4 kN
Maximum Capacity / Filling Slot	No
Fatigue load limit P_u	0.355 kN
Calculation factor k_r	0.03
Calculation factor f_0	14.7
Fatigue load limit - P_u	0.355 kN
Calculation factor - k_r	0.03
Calculation factor - f_0	14.7
Basic static load rating C_0	8.15 kN
Basic static load rating - C_0	8.2 kN