




Bearing No. S7017 CE/P4A

D	130 mm
d	85 mm
B	22 mm
a	25.5 mm
Ball - z	26
Size (mm)	130x85x22
Width (mm)	22
Mass bearing	0.94 kg
D ₂	117.6 mm
d ₂	98 mm
d ₁	100.83 mm
d ₂	98 mm
D ₂	117.6 mm
d ₁	100.83 mm
Bearing number	S7017 CE/P4A
Preload class B	118 N/micron
Preload class A	75 N/micron
Preload class C	163 N/micron
Number of balls z	26
Bore Diameter (mm)	130
d _a min.	91 mm
d _a max.	100.1 mm
d _b min.	91 mm
d _b max.	97.3 mm
D _a max.	124 mm
D _b max.	125.8 mm
r _a max.	1 mm
r _b max.	0.6 mm
Outer Diameter (mm)	85
r _{3,4} min.	0.6 mm

d_b - min.	91 mm
Calculation factor f	1.11
d_a - max.	100.1 mm
$r_{1,2}$ min.	1.1 mm
D_a - max.	124 mm
d_b - max.	97.3 mm
D_b - max.	125.8 mm
r_a - max.	1 mm
d_a - min.	91 mm
Ball - D_w	11.112 mm
r_b - max.	0.6 mm
$r_{3,4}$ - min.	0.6 mm
Calculation factor - f	1.11
$r_{1,2}$ - min.	1.1 mm
Basic dynamic load rating C	34.5 kN
Ball diameter D_w	11.112 mm
Basic dynamic load rating - C	34.5 kN
Preload class A G_A	185 N
Preload class B G_B	560 N
Preload class C G_C	1110 N
Preload class A - G_A	185 N
Preload class B - G_B	560 N
Preload class C - G_C	1110 N
Fatigue load limit P_u	1.2 kN
Calculation factor f_1	1
Calculation factor f_0	9.5
Calculation factor f_{2C}	1.05
Calculation factor f_{HC}	1
Calculation factor f_{2B}	1.03
Calculation factor f_{2A}	1

Calculation factor - f	1
Calculation factor - f_0	9.5
Fatigue load limit - P_u	1.2 kN
Calculation factor - f_{2A}	1
Calculation factor - f_{2C}	1.05
Calculation factor - f_{2B}	1.03
Calculation factor - f_{HC}	1
Limiting speed for grease lubrication	14000 r/min
Basic static load rating C_0	29 kN
Static axial stiffness, preload class B	118 N/ μ m
Static axial stiffness, preload class C	163 N/ μ m
Static axial stiffness, preload class A	75 N/ μ m
Attainable speed for grease lubrication	14000 r/min
Basic static load rating - C_0	29 kN