



Bearing No. S7015 CE/HCP4A

D	115 mm
d	75 mm
B	20 mm
a	22.8 mm
Ball - z	26
Size (mm)	115x75x20
Width (mm)	20
Mass bearing	0.62 kg
D <sub>2</sub>	104.1 mm
d <sub>2</sub>	86.8 mm
d <sub>1</sub>	89.28 mm
d <sub>2</sub>	86.8 mm
D <sub>2</sub>	104.1 mm
d <sub>1</sub>	89.28 mm
Bearing number	S7015 CE/HCP4A
Preload class B	113 N/micron
Preload class A	72 N/micron
Preload class C	156 N/micron
Number of balls z	26
Bore Diameter (mm)	115
d <sub>a</sub> min.	81 mm
d <sub>a</sub> max.	88.5 mm
d <sub>b</sub> min.	81 mm
d <sub>b</sub> max.	86 mm
D <sub>a</sub> max.	109 mm
D <sub>b</sub> max.	110.8 mm
r <sub>a</sub> max.	1 mm
r <sub>b</sub> max.	0.6 mm
Outer Diameter (mm)	75
r <sub>3,4</sub> min.	0.6 mm

$d_b$ - min.	81 mm
Calculation factor $f$	1.1
$d_a$ - max.	88.5 mm
$r_{1,2}$ min.	1.1 mm
$D_a$ - max.	109 mm
$d_b$ - max.	86 mm
$D_b$ - max.	110.8 mm
$r_a$ - max.	1 mm
$d_a$ - min.	81 mm
Ball - $D_w$	9.525 mm
$r_b$ - max.	0.6 mm
$r_{3,4}$ - min.	0.6 mm
Calculation factor - $f$	1.1
$r_{1,2}$ - min.	1.1 mm
Basic dynamic load rating C	26 kN
Ball diameter $D_w$	9.525 mm
Basic dynamic load rating - C	26 kN
Preload class A $G_A$	140 N
Preload class B $G_B$	420 N
Preload class C $G_C$	840 N
Preload class A - $G_A$	140 N
Preload class B - $G_B$	420 N
Preload class C - $G_C$	840 N
Fatigue load limit $P_u$	0.915 kN
Calculation factor $f_1$	1
Calculation factor $f_0$	9.5
Calculation factor $f_{2C}$	1.05
Calculation factor $f_{HC}$	1.01
Calculation factor $f_{2B}$	1.03
Calculation factor $f_{2A}$	1

Calculation factor - $f$	1
Calculation factor - $f_0$	9.5
Fatigue load limit - $P_u$	0.915 kN
Calculation factor - $f_{2A}$	1
Calculation factor - $f_{2C}$	1.05
Calculation factor - $f_{2B}$	1.03
Calculation factor - $f_{HC}$	1.01
Limiting speed for grease lubrication	19000 r/min
Basic static load rating $C_0$	21.6 kN
Static axial stiffness, preload class B	113 N/ $\mu$ m
Static axial stiffness, preload class C	156 N/ $\mu$ m
Static axial stiffness, preload class A	72 N/ $\mu$ m
Attainable speed for grease lubrication	19000 r/min
Basic static load rating - $C_0$	21.6 kN