



Bearing No. S7015 CE/P4A

D	115 mm
d	75 mm
B	20 mm
a	22.8 mm
Ball - z	26
Size (mm)	115x75x20
Width (mm)	20
Mass bearing	0.67 kg
D ₂	104.1 mm
d ₂	86.8 mm
d ₁	89.28 mm
d ₂	86.8 mm
D ₂	104.1 mm
d ₁	89.28 mm
Bearing number	S7015 CE/P4A
Preload class B	102 N/micron
Preload class A	65 N/micron
Preload class C	140 N/micron
Number of balls z	26
Bore Diameter (mm)	115
d _a min.	81 mm
d _a max.	88.5 mm
d _b min.	81 mm
d _b max.	86 mm
D _a max.	109 mm
D _b max.	110.8 mm
r _a max.	1 mm
r _b max.	0.6 mm
Outer Diameter (mm)	75
r _{3,4} min.	0.6 mm

d_b - min.	81 mm
Calculation factor f	1.1
d_a - max.	88.5 mm
$r_{1,2}$ min.	1.1 mm
D_a - max.	109 mm
d_b - max.	86 mm
D_b - max.	110.8 mm
r_a - max.	1 mm
d_a - min.	81 mm
Ball - D_w	9.525 mm
r_b - max.	0.6 mm
$r_{3,4}$ - min.	0.6 mm
Calculation factor - f	1.1
$r_{1,2}$ - min.	1.1 mm
Basic dynamic load rating C	26 kN
Ball diameter D_w	9.525 mm
Basic dynamic load rating - C	26 kN
Preload class A G_A	140 N
Preload class B G_B	420 N
Preload class C G_C	840 N
Preload class A - G_A	140 N
Preload class B - G_B	420 N
Preload class C - G_C	840 N
Fatigue load limit P_u	0.915 kN
Calculation factor f_1	1
Calculation factor f_0	9.5
Calculation factor f_{2C}	1.05
Calculation factor f_{HC}	1
Calculation factor f_{2B}	1.03
Calculation factor f_{2A}	1

Calculation factor - f	1
Calculation factor - f_0	9.5
Fatigue load limit - P_u	0.915 kN
Calculation factor - f_{2A}	1
Calculation factor - f_{2C}	1.05
Calculation factor - f_{2B}	1.03
Calculation factor - f_{HC}	1
Limiting speed for grease lubrication	16000 r/min
Basic static load rating C_0	21.6 kN
Static axial stiffness, preload class B	102 N/ μ m
Static axial stiffness, preload class C	140 N/ μ m
Static axial stiffness, preload class A	65 N/ μ m
Attainable speed for grease lubrication	16000 r/min
Basic static load rating - C_0	21.6 kN