



Bearing No. XAA32004X/Y32004X

|                                 |                   |
|---------------------------------|-------------------|
| R                               | 2 mm              |
| d                               | 20 mm             |
| D                               | 42 mm             |
| T                               | 15 mm             |
| B                               | 15 mm             |
| C                               | 12 mm             |
| r                               | 0,6 mm            |
| Da                              | 39,5 mm           |
| Ab                              | 1,4 mm            |
| Aa                              | 0,4 mm            |
| Db                              | 37 mm             |
| da                              | 25,5 mm           |
| db                              | 29 mm             |
| a -                             | 4,6 mm            |
| Weight                          | 0,1 Kg            |
| Size (mm)                       | 20x42x15          |
| Width (mm)                      | 15                |
| Factor (K)                      | 1,56              |
| Factor (G1)                     | 6,2               |
| Factor (Cg)                     | 0,0102            |
| Factor (G2)                     | 6,1               |
| Bearing number                  | XAA32004X/Y32004X |
| Bore Diameter (mm)              | 20                |
| Outer Diameter (mm)             | 42                |
| Calculation factor (e)          | 0,37              |
| Basic static load rating (C0)   | 29,4 kN           |
| Basic dynamic load rating (C1)  | 25,7 kN           |
| Basic dynamic load rating (C90) | 6,66              |



|                                  |      |
|----------------------------------|------|
| Basic dynamic load rating (Ca90) | 4,26 |
|----------------------------------|------|