




Bearing No. S7000 ACE/HCP4A

D	26 mm
d	10 mm
B	8 mm
a	8.3 mm
Ball - z	11
Size (mm)	26x10x8
Width (mm)	8
Mass bearing	0.017 kg
D ₂	22.35 mm
d ₂	14.5 mm
d ₁	15.6 mm
d ₂	14.5 mm
D ₂	22.35 mm
d ₁	15.6 mm
Bearing number	S7000 ACE/HCP4A
Preload class A	34 N/micron
Preload class B	52 N/micron
Preload class C	68 N/micron
Number of balls z	11
r _b max.	0.3 mm
r _a max.	0.3 mm
D _b max.	23.6 mm
D _a max.	24 mm
d _b max.	14.1 mm
d _b min.	12 mm
d _a max.	15.2 mm
Bore Diameter (mm)	26
d _a min.	12 mm
Outer Diameter (mm)	10
d _a - max.	15.2 mm

d_a - min.	12 mm
Calculation factor e	0.68
Calculation factor f	1.03
d_b - max.	14.1 mm
D_a - max.	24 mm
r_a - max.	0.3 mm
r_b - max.	0.3 mm
d_b - min.	12 mm
$r_{3,4}$ min.	0.3 mm
$r_{1,2}$ min.	0.3 mm
Ball - D_w	3.969 mm
D_b - max.	23.6 mm
$r_{3,4}$ - min.	0.3 mm
Calculation factor - f	1.03
Calculation factor - e	0.68
$r_{1,2}$ - min.	0.3 mm
Basic dynamic load rating C	2.86 kN
Ball diameter D_w	3.969 mm
Preload class A G_A	26 N
Basic dynamic load rating - C	2.9 kN
Preload class C G_C	160 N
Preload class B G_B	80 N
Preload class B - G_B	80 N
Preload class A - G_A	26 N
Preload class C - G_C	160 N
Calculation factor f_1	0.99
Fatigue load limit P_u	0.048 kN
Calculation factor f_{HC}	1.01
Calculation factor f_{2C}	1.06
Calculation factor f_{2B}	1.03

Calculation factor f_{2A}	1
Calculation factor - X_2	0.67
Calculation factor - Y_0	0.76
Calculation factor - Y_1	0.92
Calculation factor - f_1	0.99
Calculation factor - Y_2	1.41
Fatigue load limit - P_u	0.048 kN
Calculation factor - f_{2A}	1
Calculation factor - f_{2B}	1.03
Calculation factor - f_{2C}	1.06
Calculation factor - f_{HC}	1.01
Limiting speed for grease lubrication	98000 r/min
Basic static load rating C_0	1.14 kN
Static axial stiffness, preload class C	68 N/ μ m
Static axial stiffness, preload class B	52 N/ μ m
Attainable speed for grease lubrication	98000 r/min
Static axial stiffness, preload class A	34 N/ μ m
Basic static load rating - C_0	1.1 kN
Calculation factor (single, tandem) Y_2	0.87
Calculation factor (single, tandem) Y_0	0.38
Calculation factor (single, tandem) X_2	0.41
Calculation factor (back-to-back, face-to-face) Y_1	0.92
Calculation factor (back-	1.41

to-back, face-to-face) Y_2	
Calculation factor (back-to-back, face-to-face) Y_0	0.76
Calculation factor (back-to-back, face-to-face) X_2	0.67